

Product Portfolio 2017

Valves | Actuators | Automation



Type Series Index

| | | | | | |
|-----------------------------|----|-------------------------------|----|--------------------|----|
| ACTAIR | 63 | ECOLINE GTC 150-600 | 37 | SISTO-LAE | 62 |
| ACTAIR NG | 63 | ECOLINE GTF 150-600 | 38 | SISTO-LAP | 64 |
| ACTELEC (AUMA) | 62 | ECOLINE GTF 800-2500 | 38 | SISTO-RSK/RSKS | 45 |
| ACTELEC (BERNARD CONTROLS) | 62 | ECOLINE GTV 150-300 | 38 | SISTO-RSKNA | 47 |
| AKG-A/AKGS-A | 37 | ECOLINE PTF 150-600 | 42 | SISTO-VentNA | 35 |
| AKR/AKRS | 44 | ECOLINE PTF 800-2500 | 42 | SMARTRONIC AS-i | 68 |
| AMTROBOX | 66 | ECOLINE SCC 150-600 | 45 | SMARTRONIC MA | 68 |
| AMTROBOX ATEX Zone 22 | 66 | ECOLINE SCF 150-600 | 46 | SMARTRONIC PC | 68 |
| AMTROBOX C | 66 | ECOLINE SCF 800-2500 | 46 | STAAL 100 AKD/AKDS | 37 |
| AMTROBOX EEx ia | 66 | ECOLINE SCV 150-300 | 46 | STAAL 100 AKK/AKKS | 44 |
| AMTROBOX M | 66 | ECOLINE SP/SO | 36 | STAAL 40 AKD/AKDS | 36 |
| AMTROBOX R | 67 | ECOLINE VA 16 | 28 | STAAL 40 AKK/AKKS | 44 |
| AMTROBOX R EEx ia | 67 | ECOLINE WT/WTI | 44 | | |
| AMTROBOX R Ex d | 67 | | | TRIODIS 150 | 53 |
| AMTRONIC | 67 | HERA-BD | 40 | TRIODIS 300 | 54 |
| APORIS-DEB02 | 52 | HERA-BDS | 40 | TRIODIS 600 | 54 |
| | | HERA-BHT | 40 | | |
| BOACHEM-FSA | 48 | HERA-SH | 40 | UGS | 39 |
| BOACHEM-RXA | 42 | HQ | 62 | | |
| BOACHEM-ZXA | 28 | | | WADA GL 150 | 30 |
| BOACHEM-ZXAB | 26 | ISORIA 10/16 | 51 | WADA GT 150 | 39 |
| BOA-Compact | 24 | ISORIA 20 UL | 51 | WADA SC 150 | 43 |
| BOA-Compact EKB | 24 | ISORIA 20/25 | 51 | WADA SC 150 | 47 |
| BOA-Control SAR | 33 | | | ZJSVM/RJSVM | 59 |
| BOA-Control/BOA-Control IMS | 33 | KE ELASTOMER | 52 | ZRN | 47 |
| BOA-CVE C/CS/W/IMS/EKB | 32 | KE PLASTOMER | 52 | ZRS | 45 |
| BOA-CVE H | 32 | | | ZTN | 39 |
| BOA-CVP H | 32 | MAMMOUTH | 52 | ZTS | 37 |
| BOA-H | 25 | MN | 61 | ZXNB | 30 |
| BOA-H Mat E | 31 | MP-CI/MP-II | 55 | ZXNVB | 30 |
| BOA-H Mat P | 31 | MR | 61 | ZYNB/ZYN | 30 |
| BOA-H/HE/HV/HEV | 25 | | | | |
| BOA-R | 41 | NORI 160 RXL/RXS | 42 | | |
| BOA-RFV | 41 | NORI 160 ZXL/ZXS | 27 | | |
| BOA-RPL | 41 | NORI 160 ZXLF/ZXSF | 27 | | |
| BOA-RVK | 41 | NORI 320 ZXSX | 27 | | |
| BOA-S | 48 | NORI 40 FSL/FSS | 48 | | |
| BOA-SuperCompact | 24 | NORI 40 RXL/RXS | 41 | | |
| BOA-Systronic | 31 | NORI 40 ZXL/ZXS | 27 | | |
| BOAVENT-AVF | 34 | NORI 40 ZXLB/ZXSB | 25 | | |
| BOAVENT-SIF | 34 | NORI 40 ZXLBV/ZXSXBV | 25 | | |
| BOAVENT-SVA | 35 | NORI 40 ZXLF/ZXSX | 27 | | |
| BOAVENT-SVF | 35 | NORI 40 ZYLB/ZYSB | 26 | | |
| BOA-W | 24 | NORI 500 ZXSX | 28 | | |
| BOAX-B | 50 | NUCA/-A/-ES, Type V | 43 | | |
| BOAX-B APSAD | 50 | NUCA/-A/-ES, Types I, II, IV | 30 | | |
| BOAX-B DVGW | 50 | | | | |
| BOAX-B FM | 51 | PROFIN-SI3FIT/-SI3IT/-SI3LIT | 56 | | |
| BOAX-B Gaz | 50 | PROFIN-VT1 | 55 | | |
| BOAX-CBV13 | 49 | PROFIN-VT2L | 56 | | |
| BOAX-S/SF | 49 | PROFIN-VT3/-VT3L/-VT3F/-VT33L | 56 | | |
| BOAX-S/SF Gaz | 49 | | | | |
| | | RGS | 42 | | |
| CLOSSIA | 54 | RJN | 43 | | |
| COBRA-SCBS | 44 | RMD | 65 | | |
| COBRA-SGP/SGO/SGF | 36 | RYN | 43 | | |
| COBRA-SMP | 36 | | | | |
| COBRA-TDC01/03 | 47 | S/SR/SP | 61 | | |
| CONDA-VLC | 33 | SERIE 2000 | 45 | | |
| CONDA-VRC | 34 | SICCA 150-600 GLC | 29 | | |
| CONDA-VSM | 34 | SICCA 150-600 GTC | 38 | | |
| CR/CM | 61 | SICCA 150-600 SCC | 46 | | |
| | | SICCA 800-1500 GTF | 39 | | |
| DANAIS 150 | 53 | SICCA 800-4500 GLF | 29 | | |
| DANAIS MTII | 53 | SICCA 800-4500 PCF | 43 | | |
| DANAIS TBTII | 53 | SICCA 900-2500 GLC | 29 | | |
| DUALIS | 55 | SICCA 900-3600 GTC | 38 | | |
| DYNACTAIR | 63 | SICCA 900-3600 SCC | 46 | | |
| DYNACTAIR NG | 64 | SISTO-10 | 57 | | |
| | | SISTO-10M | 57 | | |
| ECOLINE BLC 1000 | 56 | SISTO-16 | 57 | | |
| ECOLINE BLT 150-300 | 55 | SISTO-16RGA | 58 | | |
| ECOLINE FYC 150-600 | 48 | SISTO-16S | 58 | | |
| ECOLINE FYF 800 | 49 | SISTO-16TWA/HWA/DLU | 58 | | |
| ECOLINE GE1/GE2/GE3 | 59 | SISTO-20 | 58 | | |
| ECOLINE GE4 | 60 | SISTO-20NA | 59 | | |
| ECOLINE GLB 150-600 | 26 | SISTO-C | 58 | | |
| ECOLINE GLB 800 | 26 | SISTO-C LAP | 64 | | |
| ECOLINE GLC 150-600 | 28 | SISTO-DrainNA | 59 | | |
| ECOLINE GLF 150-600 | 28 | SISTO-KB | 57 | | |
| ECOLINE GLF 800-2500 | 29 | SISTO-KBS | 57 | | |
| ECOLINE GLV 150-300 | 29 | SISTO-KRVNA | 35 | | |
| ECOLINE GT 40 | 36 | SISTO-LAD | 64 | | |
| ECOLINE GTB 800 | 37 | | | | |

Our tradition:

Competence since 1871

We have supplied generations of customers worldwide with pumps, valves, automation products and services. A company with that kind of experience knows that success is a process based on a stream of innovations. A process made possible by a close working alliance between developer and user, between production and practice.

Partners achieve more together.

We do everything possible to ensure that our customers always have access to the ideal product and system solution.

KSB is a loyal partner. And a strong one:

- Over 140 years' experience
- Present in more than 100 countries
- More than 16,000 employees
- More than 170 service centres worldwide
- Approximately 3,000 service specialists



Single-source supplier: your partner for pumps, valves and service

We assist our customers right through the product life cycle

A comprehensive product range, short response times and tailored service and spare parts solutions – no other competitor offers a comparable range of products and services. In all phases of the product life cycle, we are on hand to ensure that our customers secure long-term value from their systems.

We offer our customers a variety of services and spare parts solutions around pumps, valves, and other rotating equipment – also for non-KSB products:

- Technical consultancy
- Installation and commissioning
- Services provided on-site and in our service centres
- Inspection and maintenance
- Maintenance inspection management
- Framework agreements such as TPM® Total Pump Management
- Efficiency analysis with SES System Efficiency Service or Pump Operation Check
- Reverse engineering
- Inventory management
- Retrofitting as an alternative to buying a new product
- Spare parts in manufacturer's quality
- On-site training sessions
- Refurbishment and decommissioning

Ready wherever you are:
with a global service network and a 24-hour emergency service.



Our mission:

Certified quality assurance

First-class products and excellent service take top priority at KSB. To maintain this level of excellence, we have developed a modern quality management system with globally applicable guidelines. It is based on the Business Excellence model of the European Foundation for Quality Management, which already ensures improved quality management Europe-wide.

Our guidelines define uniform quality for all KSB locations and have helped us to optimise our manufacturing processes. The results are shorter delivery times and global availability of our products. These guidelines govern the way we act so comprehensively that even the competence of our consulting and the good value for money we offer are clearly stipulated. Like the 'Made in Germany' quality seal, we introduced internal certification as a sign of the highest quality: 'Made by KSB'.

Our five key goals:

- **Maximum customer satisfaction:** We do everything to fulfil our customers' wishes on time and in full.
- **Fostering quality awareness:** We put our quality commitment into daily practice – from executives to employees, whose qualifications and competence we foster through continuing training.
- **Prevention rather than cure:** We systematically analyse errors and prevent the causes.
- **Improvement in quality:** We continually optimise our processes in order to work more efficiently.
- **Involvement of suppliers:** We attach great importance to working together fairly and openly to achieve our shared goals.



As a signatory to the United Nations Global Compact, KSB is committed to endorsing the ten principles of the international community in the areas of human rights, labour standards, environmental protection and anti-corruption.



KSB Trademarks

Apart from the KSB umbrella brand, the following brand names identify quality products and services by the KSB Group:

amri

Butterfly valves

Under the AMRI brand, KSB sells its butterfly valves. They are used in building services, industry, water engineering and power generation applications. AMRI products include pneumatic, hydraulic and electric valve actuators as well as control systems.






SISTO®

Diaphragm valves

Under the SISTO brand, KSB sells its diaphragm valves. They perform shut-off duties in building services, industrial, water management and power generation applications. Under this brand name, KSB offers special valves for sterile processes including biotech applications.



General Information

| | |
|--------------------------|---|
| Regional products | Not all depicted products are available for sale in every country. Products only available in individual regions are indicated accordingly. Please contact your sales representative for details. |
| Key to actuators | In the Products section from page 24 the symbol  in conjunction with the relevant letter indicates the actuator type(s) available.  m = manual (lever, handwheel, etc.)  e = electric actuator  p = pneumatic actuator  h = hydraulic actuator |
| Trademark rights | All trademarks or company logos shown in the catalogue are protected by trademark rights owned by KSB Aktiengesellschaft and/or a KSB Group company. The absence of the "®" symbol should not be interpreted to mean that the term is not a registered trademark. |

Valves

| Design/Application | Type series | Page | Automation | Water Transport and Treatment | Industry | Energy Conversion | Building Services | Solids Transport | Pharmaceuticals/ Food |
|---|------------------------------|------|------------|-------------------------------|----------|-------------------|-------------------|------------------|-----------------------|
| Soft-seated globe valves to DIN/EN | BOA-SuperCompact | 24 | ■ | | ■ | | ■ | | |
| | BOA-Compact | 24 | ■ | | ■ | | ■ | | |
| | BOA-Compact EKB | 24 | ■ | | ■ | | ■ | | |
| | BOA-W | 24 | ■ | ■ | ■ | | ■ | | |
| Bellows-type globe valves to DIN/EN | BOA-H | 25 | | | ■ | ■ | ■ | | |
| | BOA-H/HE/HV/HEV | 25 | ■ | | ■ | ■ | ■ | | |
| | NORI 40 ZXLBV/ZXSBV | 25 | | | ■ | ■ | ■ | | |
| | NORI 40 ZXLB/ZXSB | 25 | ■ | | ■ | ■ | ■ | | |
| | NORI 40 ZYLB/ZYSB | 26 | | | ■ | ■ | ■ | | |
| | BOACHEM-ZXAB | 26 | ■ | | ■ | ■ | ■ | | |
| Bellows-type globe valves to ANSI/ASME | ECOLINE GLB 150-600 | 26 | ■ | | ■ | ■ | | | ■ |
| | ECOLINE GLB 800 | 26 | ■ | | ■ | ■ | | | ■ |
| Globe valves to DIN/EN with gland packing | NORI 40 ZXLF/ZXS | 27 | | | ■ | ■ | ■ | | |
| | NORI 40 ZXLF/ZXS | 27 | ■ | | ■ | ■ | ■ | | |
| | NORI 160 ZXLF/ZXS | 27 | | | ■ | ■ | | | |
| | NORI 160 ZXLF/ZXS | 27 | ■ | | ■ | ■ | | | |
| | NORI 320 ZXS | 27 | ■ | | ■ | ■ | | | |
| | NORI 500 ZXS | 28 | ■ | | ■ | ■ | | | |
| | BOACHEM-ZXA | 28 | | | ■ | | ■ | | |
| | ECOLINE VA 16 | 28 | | | ■ | | ■ | | |
| Globe valve to ANSI/ASME with gland packing | ECOLINE GLC 150-600 | 28 | ■ | | ■ | ■ | | | |
| | ECOLINE GLF 150-600 | 28 | ■ | | ■ | ■ | | | |
| | ECOLINE GLF 800-2500 | 29 | ■ | | ■ | ■ | | | |
| | ECOLINE GLV 150-300 | 29 | ■ | | ■ | ■ | | | |
| | SICCA 150-600 GLC | 29 | ■ | | ■ | ■ | | | |
| | SICCA 900-2500 GLC | 29 | ■ | | ■ | ■ | | | |
| | SICCA 800-4500 GLF | 29 | ■ | | ■ | ■ | | | |
| | WADA GL 150 | 30 | ■ | | ■ | | | | |
| Globe valves for nuclear applications | NUCA/-A/-ES, Types I, II, IV | 30 | ■ | | | ■ | | | |
| | ZXNB | 30 | ■ | | | ■ | | | |
| | ZXNVB | 30 | | | | ■ | | | |
| | ZYNB/ZYN | 30 | ■ | | | ■ | | | |
| Control systems to DIN/EN | BOA-Systronic | 31 | ■ | | | | ■ | | |
| Automated globe valves to DIN/EN | BOA-H Mat E | 31 | ■ | | ■ | ■ | ■ | | |
| | BOA-H Mat P | 31 | ■ | | ■ | ■ | ■ | | |
| Control valves to DIN/EN | BOA-CVE C/CS/W/IMS/EKB | 32 | ■ | ■ | ■ | | ■ | | |
| | BOA-CVE H | 32 | ■ | | ■ | ■ | ■ | | |
| | BOA-CVP H | 32 | ■ | | ■ | ■ | ■ | | |
| Balancing and shut-off valves to DIN/EN | BOA-Control/BOA-Control IMS | 33 | ■ | | ■ | | ■ | | |
| | BOA-Control SAR | 33 | | | ■ | | ■ | | |
| Level control valves to DIN/EN | CONDA-VLC | 33 | | ■ | | | | | |
| Pressure reducing valves to DIN/EN | CONDA-VRC | 34 | | ■ | | | | | |
| Pressure sustaining valves to DIN/EN | CONDA-VSM | 34 | | ■ | | | | | |
| Air valves to DIN/EN | BOAVENT-AVF | 34 | | ■ | | | | | |
| | BOAVENT-SIF | 34 | | ■ | | | | | |
| | BOAVENT-SVA | 35 | | ■ | | | | | |
| | BOAVENT-SVF | 35 | | ■ | | | | | |
| Vent valves for nuclear applications | SISTO-VentNA | 35 | | | | ■ | ■ | | |
| | SISTO-KRVNA | 35 | | | | ■ | | | |

| Design/Application | Type series | Page | Automation | Water Transport and Treatment | Industry | Energy Conversion | Building Services | Solids Transport | Pharmaceuticals/ Food |
|---|----------------------|------|------------|-------------------------------|----------|-------------------|-------------------|------------------|-----------------------|
| Gate valves to DIN/EN | COBRA-SGP/SGO/SGF | 36 | | ■ | ■ | | ■ | | |
| | COBRA-SMP | 36 | | ■ | ■ | | ■ | | |
| | ECOLINE SP/SO | 36 | | ■ | ■ | | ■ | | |
| | ECOLINE GT 40 | 36 | ■ | | ■ | | | | |
| | STAAL 40 AKD/AKDS | 36 | ■ | | ■ | ■ | | | |
| | STAAL 100 AKD/AKDS | 37 | ■ | | ■ | ■ | | | |
| | AKG-A/AKGS-A | 37 | ■ | | ■ | ■ | | | |
| | ZTS | 37 | ■ | | ■ | ■ | | | |
| Gate valves to ANSI/ASME | ECOLINE GTB 800 | 37 | ■ | | ■ | ■ | | | ■ |
| | ECOLINE GTC 150-600 | 37 | ■ | | ■ | ■ | | | |
| | ECOLINE GTF 150-600 | 38 | ■ | | ■ | ■ | | | |
| | ECOLINE GTF 800-2500 | 38 | ■ | | ■ | ■ | | | |
| | ECOLINE GTV 150-300 | 38 | ■ | | ■ | ■ | | | |
| | SICCA 150-600 GTC | 38 | ■ | | ■ | ■ | | | |
| | SICCA 900-3600 GTC | 38 | ■ | | ■ | ■ | | | |
| | SICCA 800-1500 GTF | 39 | ■ | | ■ | ■ | | | |
| Gate valves for nuclear applications | WADA GT 150 | 39 | ■ | | ■ | | | | |
| Body pressure relief valve | ZTN | 39 | ■ | | | ■ | | | |
| Knife gate valves to DIN/EN | UGS | 39 | | | ■ | ■ | | | |
| Knife gate valves to ANSI/ASME | HERA-BD | 40 | ■ | ■ | ■ | | ■ | ■ | |
| | HERA-BDS | 40 | ■ | ■ | ■ | | | ■ | |
| | HERA-BHT | 40 | ■ | ■ | ■ | | | ■ | |
| | HERA-SH | 40 | ■ | ■ | ■ | | | ■ | |
| Lift check valves to DIN/EN | BOA-RPL | 41 | | ■ | | | ■ | | |
| | BOA-RFV | 41 | | ■ | ■ | | ■ | | |
| | BOA-RVK | 41 | | | ■ | ■ | ■ | | |
| | BOA-R | 41 | | | ■ | ■ | ■ | | |
| | NORI 40 RXL/RXS | 41 | | | ■ | ■ | ■ | | |
| | NORI 160 RXL/RXS | 42 | | | ■ | ■ | ■ | | |
| | RGS | 42 | | | ■ | ■ | | | |
| | BOACHEM-RXA | 42 | | | ■ | | ■ | | |
| Lift check valves to ANSI/ASME | ECOLINE PTF 150-600 | 42 | | | ■ | ■ | | | |
| | ECOLINE PTF 800-2500 | 42 | | | ■ | ■ | | | |
| | SICCA 800-4500 PCF | 43 | | | ■ | ■ | | | |
| | WADA SC 150 | 43 | | | ■ | | | | |
| Lift check valves for nuclear applications | NUCA/-A/-ES, Type V | 43 | | | | ■ | | | |
| | RJN | 43 | | | | ■ | | | |
| | RYN | 43 | ■ | | | ■ | | | |
| Swing check valves to DIN/EN | COBRA-SCBS | 44 | | ■ | ■ | | ■ | | |
| | ECOLINE WT/WTI | 44 | | | ■ | | ■ | | |
| | STAAL 40 AKK/AKKS | 44 | | | ■ | ■ | | | |
| | STAAL 100 AKK/AKKS | 44 | | | ■ | ■ | | | |
| | AKR/AKRS | 44 | | | ■ | ■ | | | |
| | ZRS | 45 | | | ■ | ■ | | | |
| | SISTO-RSK/RSKS | 45 | | ■ | ■ | ■ | | ■ | |
| | SERIE 2000 | 45 | | ■ | ■ | | ■ | | |
| Swing check valves to ANSI/ASME | ECOLINE SCC 150-600 | 45 | | | ■ | ■ | | | |
| | ECOLINE SCF 150-600 | 46 | | | ■ | ■ | | | |
| | ECOLINE SCF 800-2500 | 46 | | | ■ | ■ | | | |
| | ECOLINE SCV 150-300 | 46 | | | ■ | ■ | | | |
| | SICCA 150-600 SCC | 46 | | | ■ | ■ | | | |
| | SICCA 900-3600 SCC | 46 | | | ■ | ■ | | | |
| | WADA SC 150 | 47 | | | ■ | | | | |
| Swing check valves for nuclear applications | SISTO-RSKNA | 47 | | | | ■ | | | |
| | ZRN | 47 | | | | ■ | | | |
| Tilting disc check valves to DIN/EN | COBRA-TDC01/03 | 47 | | ■ | ■ | ■ | | | |

| Design/Application | Type series | Page | Automation | Water Transport and Treatment | Industry | Energy Conversion | Building Services | Solids Transport | Pharmaceuticals/ Food |
|---|--------------------------------|--------------|------------|-------------------------------|----------|-------------------|-------------------|------------------|-----------------------|
| Strainers to DIN/EN | BOA-S | 48 | | | ■ | ■ | ■ | | |
| | NORI 40 FSL/FSS | 48 | | | ■ | ■ | ■ | | |
| | BOACHEM-FSA | 48 | | | ■ | | ■ | | |
| Strainers to ANSI/ASME | ECOLINE FYC 150-600 | 48 | | | ■ | ■ | | | |
| | ECOLINE FYF 800 | 49 | | | ■ | ■ | | | |
| Centred-disc butterfly valves | BOAX-CBV13 | 49 | | ■ | ■ | ■ | ■ | | |
| | BOAX-S/SF | 49 | ■ | | | | ■ | | |
| | BOAX-S/SF Gaz | 49 | | | | | ■ | | |
| | BOAX-B | 50 | ■ | ■ | ■ | | ■ | | |
| | BOAX-B Gaz | 50 | | ■ | ■ | | ■ | | |
| | BOAX-B APSAD | 50 | | | ■ | | ■ | | |
| | BOAX-B DVGW | 50 | | ■ | ■ | | ■ | | |
| | BOAX-B FM | 51 | | | ■ | | ■ | | |
| | ISORIA 10/16 | 51 | ■ | ■ | ■ | ■ | ■ | ■ | |
| | ISORIA 20/25 | 51 | ■ | ■ | ■ | ■ | ■ | | |
| | ISORIA 20 UL | 51 | ■ | | ■ | | | | |
| | MAMMOUTH | 52 | ■ | ■ | ■ | ■ | | | |
| | KE PLASTOMER | 52 | ■ | ■ | ■ | | | | |
| | KE ELASTOMER | 52 | ■ | ■ | ■ | | | | |
| | Double-offset butterfly valves | APORIS-DEB02 | 52 | | ■ | ■ | ■ | | |
| DANAŠ 150 | | 53 | ■ | ■ | ■ | ■ | ■ | ■ | |
| DANAŠ MTII | | 53 | ■ | | ■ | ■ | | ■ | |
| DANAŠ TBTII | | 53 | ■ | | ■ | | | | |
| Triple-offset butterfly valves | TRIODIS 150 | 53 | ■ | | ■ | ■ | | | |
| | TRIODIS 300 | 54 | ■ | | ■ | ■ | | | |
| | TRIODIS 600 | 54 | ■ | | ■ | ■ | | | |
| Butterfly valves for nuclear applications | CLOSSIA | 54 | ■ | | | ■ | | | |
| Combined butterfly/check valves | DUALIS | 55 | | ■ | | | | | |
| Single-piece ball valves | MP-CI/MP-II | 55 | ■ | ■ | | | | | |
| | PROFIN-VT1 | 55 | | ■ | ■ | | ■ | | |
| Two-piece ball valves | ECOLINE BLT 150-300 | 55 | ■ | | ■ | ■ | | | ■ |
| | PROFIN-VT2L | 56 | | ■ | ■ | | ■ | | |
| Three-piece ball valves | ECOLINE BLC 1000 | 56 | ■ | | ■ | ■ | | | ■ |
| | PROFIN-SI3FIT/SI3IT/SI3LIT | 56 | ■ | ■ | ■ | | ■ | | |
| | PROFIN-VT3/-VT3L/-VT3F/-VT33L | 56 | | ■ | ■ | | ■ | | |
| Soft-seated diaphragm valves to DIN/EN | SISTO-KB | 57 | ■ | ■ | ■ | ■ | | ■ | |
| | SISTO-KBS | 57 | ■ | ■ | ■ | ■ | | ■ | |
| | SISTO-10 | 57 | ■ | ■ | ■ | ■ | | | |
| | SISTO-10M | 57 | ■ | ■ | ■ | ■ | ■ | | |
| | SISTO-16 | 57 | ■ | ■ | ■ | ■ | | | |
| | SISTO-16S | 58 | ■ | ■ | ■ | ■ | | | |
| | SISTO-16RGA | 58 | | ■ | | | ■ | | |
| | SISTO-16TWA/HWA/DLU | 58 | ■ | ■ | | | ■ | | |
| | SISTO-20 | 58 | ■ | | ■ | ■ | | | ■ |
| | SISTO-C | 58 | ■ | ■ | | | | | ■ |
| Diaphragm valves for nuclear applications | SISTO-20NA | 59 | ■ | | | ■ | | | |
| | SISTO-DrainNA | 59 | | | | ■ | | | |
| Feed water bypass valves | ZJSVM/RJSVM | 59 | ■ | | ■ | ■ | | | |
| Expansion and anti-vibration joints | ECOLINE GE1/GE2/GE3 | 59 | | | ■ | | ■ | | |
| | ECOLINE GE4 | 60 | | | ■ | | ■ | | |

Actuators

| Design/Application | Type series | Page | Water Transport and Treatment | Industry | Energy Conversion | Building Services | Solids Transport | Pharmaceuticals/ Food |
|---------------------|----------------------------|------|-------------------------------|----------|-------------------|-------------------|------------------|-----------------------|
| Levers | CR/CM | 61 | ■ | ■ | ■ | ■ | | |
| | S/SR/SP | 61 | ■ | ■ | ■ | ■ | | |
| Manual gearboxes | MN | 61 | ■ | ■ | | ■ | | |
| | MR | 61 | ■ | ■ | ■ | ■ | ■ | |
| Electric actuators | ACTELEC (AUMA) | 62 | ■ | ■ | ■ | ■ | | |
| | ACTELEC (BERNARD CONTROLS) | 62 | ■ | ■ | ■ | ■ | | |
| | SISTO-LAE | 62 | ■ | ■ | ■ | ■ | ■ | |
| Hydraulic actuators | HQ | 62 | ■ | ■ | ■ | | | |
| Pneumatic actuators | ACTAIR | 63 | ■ | ■ | ■ | | | |
| | ACTAIR NG | 63 | ■ | ■ | ■ | | | |
| | DYNACTAIR | 63 | ■ | ■ | ■ | | | |
| | DYNACTAIR NG | 64 | ■ | ■ | ■ | | | |
| | SISTO-LAD | 64 | ■ | ■ | ■ | ■ | ■ | |
| | SISTO-LAP | 64 | ■ | ■ | ■ | ■ | ■ | |
| | SISTO-C LAP | 64 | | | | | | ■ |
| Control accessories | RMD | 65 | ■ | ■ | ■ | ■ | | |

KSB offers a wide range of actuators. Just contact our specialists.

Automation

| Design/Application | Type series | Page | Water Transport and Treatment | Industry | Energy Conversion | Building Services | Solids Transport | Pharmaceuticals/ Food |
|--------------------------|-----------------------|------|-------------------------------|----------|-------------------|-------------------|------------------|-----------------------|
| Monitoring | AMTROBOX | 66 | ■ | ■ | ■ | | | |
| | AMTROBOX EEx ia | 66 | ■ | ■ | ■ | | | |
| | AMTROBOX ATEX Zone 22 | 66 | ■ | ■ | ■ | | | |
| | AMTROBOX C | 66 | ■ | ■ | ■ | ■ | | |
| | AMTROBOX M | 66 | ■ | ■ | ■ | ■ | | |
| | AMTROBOX R | 67 | ■ | ■ | ■ | | | |
| | AMTROBOX R EEx ia | 67 | ■ | ■ | ■ | | | |
| | AMTROBOX R Ex d | 67 | ■ | ■ | ■ | | | |
| ON/OFF valve controllers | AMTRONIC | 67 | ■ | ■ | ■ | | | |
| Positioners | SMARTRONIC MA | 68 | ■ | ■ | ■ | | | |
| | SMARTRONIC AS-I | 68 | ■ | ■ | ■ | | | |
| Intelligent positioners | SMARTRONIC PC | 68 | ■ | ■ | ■ | | | |

Fluids handled

| | BOA-SuperCompact BOA-Compact BOA-Compact EKB BOA-W | BOA-H BOA-H/HE/HV/HEV NORI 40 ZXLBV/ZXSBV NORI 40 ZXLB/ZXSB NORI 40 ZYLB/ZYSB BOACHEM-ZXAB | ECOLINE GLB 150-600 ECOLINE GLB 800 | NORI 40 ZXL/ZXS NORI 40 ZXLF/ZXSF NORI 160 ZXL/ZXS NORI 160 ZXLF/ZXSF NORI 320 ZXS NORI 500 ZXS BOACHEM-ZXA ECOLINE VA 16 | SICCA 150-600 GLC SICCA 900-2500 GLC SICCA 800-4500 GLF ECOLINE GLC 150-600 ECOLINE GLF 150-600 ECOLINE GLF 800-2500 WADA GL 150 |
|-----------------------------------|---|---|--|--|--|
| Abrasive fluids | | | | | |
| Waste water with faeces | | | | | |
| Waste water without faeces | | | | | |
| Aggressive fluids | | | | | |
| Inorganic fluids | | | | | |
| Activated sludge | | | | | |
| Brackish water | | | | | |
| Service water | | | | | |
| Steam | | | | | |
| Distillate | | | | | |
| Explosive fluids | | | | | |
| Digested sludge | | | | | |
| Solids-laden fluids | | | | | |
| Solids (ore, sand, gravel, ash) | | | | | |
| Flammable fluids | | | | | |
| River, lake and groundwater | | | | | |
| Liquefied gas | | | | | |
| Fluids containing gas | | | | | |
| Gases | | | | | |
| Harmful fluids | | | | | |
| Toxic fluids | | | | | |
| High-temperature hot water | | | | | |
| Heating water | | | | | |
| Highly aggressive fluids | | | | | |
| Condensate | | | | | |
| Corrosive fluids | | | | | |
| Valuable fluids | | | | | |
| Fuels | | | | | |
| Cooling water | | | | | |
| Highly volatile fluids | | | | | |
| Fire-fighting water | | | | | |
| Solvents | | | | | |
| Seawater | | | | | |
| Fluids containing mineral oils | | | | | |
| Oils | | | | | |
| Organic fluids | | | | | |
| Polymerising/crystallising fluids | | | | | |
| Radioactive fluids | | | | | |
| Cleaning agents | | | | | |
| Raw sludge | | | | | |
| Lubricants | | | | | |
| Grey water | | | | | |
| Brine | | | | | |
| Feed water | | | | | |
| Dipping paints | | | | | |
| Drinking water | | | | | |
| Vacuum | | | | | |
| Thermal oils | | | | | |
| Wash water | | | | | |

Fluids handled

| | RG5 BOACHEM-RXA | ECOLINE PTF 150-600 ECOLINE PTF 800-2500 SICCA 800-4500 PCF WADA SC 150 | NUCA-AJ-ES, Type V RJN RYN | COBRA-SCBS ECOLINE WT/WTI STAAL 40 AKK/AKKS STAAL 100 AKK/AKKS AKR/AKRS ZRS SISTO-RSK/RSKS SERIE 2000 | ECOLINE SCC 150-600 ECOLINE SCF 150-600 ECOLINE SCF 800-2500 ECOLINE SCV 150-300 SICCA 150-600 SCC SICCA 900-3600 SCC WADA SC 150 | SISTO-RSKNA ZRN | COBRA-TDC01/03 |
|-----------------------------------|--------------------|--|----------------------------------|--|---|--------------------|----------------|
| Abrasive fluids | | | | | | | |
| Waste water with faeces | | | | | | | |
| Waste water without faeces | | | | | | | |
| Aggressive fluids | | | | | | | |
| Inorganic fluids | | | | | | | |
| Activated sludge | | | | | | | |
| Brackish water | | | | | | | |
| Service water | | | | | | | |
| Steam | | | | | | | |
| Distillate | | | | | | | |
| Explosive fluids | | | | | | | |
| Digested sludge | | | | | | | |
| Solids-laden fluids | | | | | | | |
| Solids (ore, sand, gravel, ash) | | | | | | | |
| Flammable fluids | | | | | | | |
| River, lake and groundwater | | | | | | | |
| Liquefied gas | | | | | | | |
| Fluids containing gas | | | | | | | |
| Gases | | | | | | | |
| Harmful fluids | | | | | | | |
| Toxic fluids | | | | | | | |
| High-temperature hot water | | | | | | | |
| Heating water | | | | | | | |
| Highly aggressive fluids | | | | | | | |
| Condensate | | | | | | | |
| Corrosive fluids | | | | | | | |
| Valuable fluids | | | | | | | |
| Fuels | | | | | | | |
| Cooling water | | | | | | | |
| Highly volatile fluids | | | | | | | |
| Fire-fighting water | | | | | | | |
| Solvents | | | | | | | |
| Seawater | | | | | | | |
| Fluids containing mineral oils | | | | | | | |
| Oils | | | | | | | |
| Organic fluids | | | | | | | |
| Polymerising/crystallising fluids | | | | | | | |
| Radioactive fluids | | | | | | | |
| Cleaning agents | | | | | | | |
| Raw sludge | | | | | | | |
| Lubricants | | | | | | | |
| Grey water | | | | | | | |
| Brine | | | | | | | |
| Feed water | | | | | | | |
| Dipping paints | | | | | | | |
| Drinking water | | | | | | | |
| Vacuum | | | | | | | |
| Thermal oils | | | | | | | |
| Wash water | | | | | | | |

Fluids handled

| | MP-CI/MP-II PROFIN-VT1 | ECOLINE BLT 150-300 PROFIN-VT2L | ECOLINE BLC 1000 PROFIN-SI3FIT PROFIN-SI3IT PROFIN-SI3LIT PROFIN-VT3 PROFIN-VT3L PROFIN-VT3F PROFIN-VT33L | SISTO-KB SISTO-KBS SISTO-10 SISTO-10M SISTO-16 SISTO-16S SISTO-16RGA SISTO-16TWA/HWA/DLU SISTO-20 SISTO-C | SISTO-20NA SISTO-DrainNA | ZISVM/RJSVM | ECOLINE GE1/GE2/GE3 ECOLINE GE4 |
|-----------------------------------|---------------------------|------------------------------------|--|--|-----------------------------|-------------|------------------------------------|
| Abrasive fluids | | | | | | | |
| Waste water with faeces | | | | | | | |
| Waste water without faeces | | | | | | | |
| Aggressive fluids | ■ | ■ | ■ | ■ | ■ | | |
| Inorganic fluids | | ■ | ■ | ■ | ■ | | |
| Activated sludge | | | | | | | |
| Brackish water | | | | | | | |
| Service water | ■ | ■ | ■ | ■ | ■ | | |
| Steam | | | | | | | |
| Distillate | | | | | | | |
| Explosive fluids | | | | | | | |
| Digested sludge | | | | | | | |
| Solids-laden fluids | | | | | | | |
| Solids (ore, sand, gravel, ash) | | | | | | | |
| Flammable fluids | ■ | | ■ | ■ | ■ | | |
| River, lake and groundwater | ■ | ■ | ■ | ■ | ■ | | ■ |
| Liquefied gas | | | | | | | |
| Fluids containing gas | | ■ | ■ | ■ | ■ | | |
| Gases | ■ | ■ | ■ | ■ | ■ | | |
| Harmful fluids | | ■ | ■ | ■ | ■ | | |
| Toxic fluids | | ■ | ■ | ■ | ■ | | |
| High-temperature hot water | ■ | ■ | ■ | ■ | ■ | | |
| Heating water | ■ | | ■ | ■ | ■ | | |
| Highly aggressive fluids | | ■ | ■ | ■ | ■ | | |
| Condensate | | ■ | ■ | ■ | ■ | | |
| Corrosive fluids | ■ | ■ | ■ | ■ | ■ | | |
| Valuable fluids | | | | | | | |
| Fuels | | ■ | ■ | ■ | ■ | | |
| Cooling water | ■ | ■ | ■ | ■ | ■ | | ■ |
| Highly volatile fluids | | | | | | | |
| Fire-fighting water | ■ | ■ | ■ | ■ | ■ | | |
| Solvents | | | ■ | ■ | ■ | | |
| Seawater | | | ■ | ■ | ■ | | |
| Fluids containing mineral oils | | | ■ | ■ | ■ | | |
| Oils | ■ | ■ | ■ | ■ | ■ | | |
| Organic fluids | | ■ | ■ | ■ | ■ | | |
| Polymerising/crystallising fluids | | | | ■ | ■ | | |
| Radioactive fluids | | | | | ■ | | |
| Cleaning agents | ■ | | ■ | ■ | ■ | | |
| Raw sludge | | | | ■ | ■ | | |
| Lubricants | | ■ | ■ | ■ | ■ | | |
| Grey water | | | | ■ | ■ | | ■ |
| Brine | | | | ■ | ■ | | ■ |
| Feed water | ■ | ■ | ■ | ■ | ■ | | ■ |
| Dipping paints | | | ■ | ■ | ■ | | |
| Drinking water | ■ | ■ | ■ | ■ | ■ | | ■ |
| Vacuum | | | | ■ | ■ | | |
| Thermal oils | | ■ | ■ | ■ | ■ | | |
| Wash water | ■ | ■ | ■ | ■ | ■ | | |

Applications

| | NUCA/A/-ES, Types I, II, IV ZYNB/ZYN ZKNB ZKNVB | BOA-Systronic | BOA-H Mat E BOA-H Mat P | BOA-CVE C/CS/W/IMS/EKB BOA-CVE H BOA-CVP H | BOA-Control /BOA-Control IMS BOA-Control SAR | CONDA-VLC | CONDA-VRC | CONDA-VSM | BOAVENT-AVF BOAVENT-SVF BOAVENT-SIF BOAVENT-SVA | SISTO-VentNA SISTO-KRVNA |
|---------------------------------------|--|---------------|----------------------------|--|---|-----------|-----------|-----------|--|-----------------------------|
| Spray irrigation | | | | | | | | | | |
| Mining | | | | | | | | | | |
| Irrigation | | | | | | | | | | |
| Chemical industry | | | ■ | ■ | | | | | | |
| Pressure boosting | | | | | | | | | | |
| Disposal | | | | | | | | | | |
| Drainage | | | | | | | | | | |
| Descaling units | | | | | | | | | | |
| District heating | | | | | | | | | | |
| Solids transport | | | | | | | | | | |
| Fire-fighting systems | | | | | | | | | | |
| Gas pipelines | | | | | | | | | | |
| Gas storage facilities | | | | | | | | | | |
| Maintaining groundwater levels | | | | | | | | | | |
| Domestic water supply | | | | | | | | | | |
| HVAC systems | | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Homogenisation | | | | | | | | | | |
| Industrial recirculation systems | | | | | | | | | | |
| Nuclear power stations | ■ | ■ | ■ | ■ | | | | | | ■ |
| Boiler feed applications | | | ■ | ■ | ■ | ■ | | | | ■ |
| Boiler recirculation | | | ■ | ■ | ■ | ■ | | | | |
| Sewage treatment plants | | | | | | | | | | |
| Air-conditioning systems | | | ■ | ■ | ■ | ■ | | | | |
| Condensate transport | | | | | | | | | | |
| Fossil-fuelled power stations | | | | | | | | | | |
| Cooling circuits | | | ■ | ■ | ■ | ■ | | | | |
| Paint shops | | | | | | | | | | |
| Food and beverages industries | | | | | | | | | | |
| Seawater desalination/reverse osmosis | | | | | | | | | | |
| Mixing | | | | | | | | | | |
| Paper and pulp industry | | | | | | | | | | |
| Petrochemical industry | | | | | | | | | | |
| Pharmaceutical industry | | | | | | | | | | |
| Pipelines and tank farms | | | | | | | | | | |
| Refineries | | | | | | | | | | |
| Flue gas desulphurisation | | | | | | | | | | |
| Rainwater harvesting | | | | | | | | | | |
| Recirculation | | | | | | | | | | |
| Shipbuilding | | | | | | | | | | |
| Sludge disposal | | | | | | | | | | |
| Sludge processing | | | | | | | | | | |
| Snow-making systems | | | ■ | | ■ | | | | | |
| Swimming pools | | | | | | | | | | |
| Keeping in suspension | | | | | | | | | | |
| Thermal oil circulation | | | ■ | ■ | ■ | ■ | | | | |
| Process engineering | | | ■ | ■ | ■ | ■ | | | | |
| Heat recovery systems | | | ■ | ■ | ■ | ■ | | | | |
| Hot-water heating systems | | ■ | ■ | ■ | ■ | ■ | | | | |
| Washing plants | | | | | | | | | | |
| Water treatment | | | | | | ■ | ■ | ■ | ■ | ■ |
| Water extraction | | | | | | ■ | ■ | ■ | ■ | ■ |
| Water supply | | | | ■ | | ■ | ■ | ■ | ■ | ■ |
| Sugar industry | | | ■ | ■ | | | | | ■ | ■ |

Soft-seated globe valves to DIN/EN

BOA-SuperCompact



PN 6/10/16
DN 20 - 200
T [°C] -10 to +120

Description:
Globe valve to DIN/EN with wafer-type body, super-compact DN face-to-face length to EN 558/94, slanted seat, bonnetless; with flange alignment holes for centring, dead-end service and downstream dismantling; insulating cap with anti-condensation feature as standard, position indicator, soft main and back seat; maintenance-free, full insulation possible.

Applications:
Hot-water heating systems up to 120 °C. Air-conditioning systems. Not suitable for fluids containing mineral oils, steam or fluids liable to attack EPDM and cast iron. Other fluids on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000312>

BOA-Compact



PN 6/16
DN 15 - 200
T [°C] -10 to +120

Description:
Globe valve to DIN/EN with flanged ends, short face-to-face length to EN 558/14, slanted seat, bonnetless, EPDM-encapsulated throttling plug, soft main and back seat, position indicator, locking device, travel stop, insulating cap with anti-condensation feature; maintenance-free, full insulation possible.

Applications:
Hot-water heating systems up to 120 °C. Air-conditioning systems. Not suitable for fluids containing mineral oils, steam or fluids liable to attack EPDM and cast iron. Other fluids on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000310>

BOA-Compact EKB



PN 10/16
DN 15 - 200
T [°C] -10 to +80

Description:
Globe valve to DIN/EN with flanged ends, compact face-to-face length for drinking water supply systems, with electrostatic plastic coating inside and outside, slanted seat, bonnetless, EPDM-encapsulated throttling plug, position indicator, locking device, travel stop, soft main and back seat; maintenance-free (PN 10 DVGW-approved).

Applications:
Water supply systems, drinking water, air-conditioning systems. Cooling circuits. Suitable for installation in copper pipes as per installation instructions (operating manual). Not suitable for fluids containing mineral oils, steam or fluids liable to attack EPDM and the electrostatic plastic coating. Other fluids on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000311>

BOA-W



PN 6/16
DN 15 - 200
T [°C] -10 to +120

Description:
Globe valve to DIN/EN with flanged ends, standard face-to-face length to EN 558/1, slanted seat, bonnetless, EPDM-encapsulated throttling plug, soft main and back seat, position indicator, locking device, travel stop, insulating cap with anti-condensation feature; maintenance-free, full insulation possible.

Applications:
Hot-water heating systems up to 120 °C. Air-conditioning systems. Not suitable for fluids containing mineral oils, steam or fluids liable to attack EPDM and cast iron. Other fluids on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000309>

Bellows-type globe valves to DIN/EN

BOA-H



| | |
|--------|-------------|
| PN | 16/25 |
| DN | 15 - 350 |
| T [°C] | -10 to +350 |

Description:
Bellows-type globe valve to DIN/EN with flanged ends, with shut-off valve disc or throttling plug, standard position indicator with colour coding for identification of valve design, replaceable valve disc; bellows protected when valve is in fully open position; seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:
Hot-water heating systems, high-temperature hot water systems, cooling circuits, heat transfer systems, general steam applications in building services and industry. Other fluids on request.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000328>

BOA-H/HE/HV/HEV



| | |
|--------|-------------|
| PN | 25/40 |
| DN | 10 - 350 |
| T [°C] | -10 to +450 |

Description:
Bellows-type globe valve to DIN/EN with flanged, butt weld or socket weld ends, with shut-off valve disc or throttling plug, seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:
In industrial plants, building services, power stations and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000329>

NORI 40 ZXLBV/ZXSBV



| | |
|--------|-------------|
| PN | 25/40 |
| DN | 10 - 200 |
| T [°C] | -10 to +450 |

Description:
Bellows-type globe valve to DIN/EN with flanged, butt weld or socket weld ends, tapered shut-off valve disc or throttling plug, two-piece stem, integrated position indicator, seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000334>

NORI 40 ZXLB/ZXSB



| | |
|--------|-------------|
| PN | 25/40 |
| DN | 10 - 200 |
| T [°C] | -10 to +450 |

Description:
Bellows-type globe valve to DIN/EN with flanged, butt weld or socket weld ends, tapered shut-off valve disc or throttling plug, two-piece stem, integrated position indicator, seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000332>

NORI 40 ZYLB/ZYSB



PN 25/40
DN 15 - 300
T [°C] -10 to +450

Description:
Bellows-type globe valve to DIN/EN with flanged or butt weld ends, Y-valve, replaceable throttling plug (up to DN 100) or shut-off valve disc (DN 125 and above), single-piece non-rotating stem, position indicator, travel stop, locking device; seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:
In heat transfer systems, industrial plants, building services and shipbuilding. For thermal oils, water, steam, gas and other non-aggressive fluids. Other fluids on request.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000521>

BOACHEM-ZXAB



PN 10 - 40
DN 15 - 200
T [°C] -10 to +400

Description:
Bellows-type globe valve to DIN/EN with flanged ends, body made of stainless steel, with replaceable shut-off valve disc or throttling plug.

Applications:
Process engineering, industry, building services, food and beverages industries, for aggressive fluids. Other fluids on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000337>

Bellows-type globe valves to ANSI/ASME

ECOLINE GLB 150-600



Class 150 - 600
NPS 2" - 12"
T [°C] 0 to +427

Description:
Globe valve to ANSI/ASME with flanged ends, cast steel/stainless steel body, trim and bellows made of stainless steel, with bolted bonnet, outside screw and yoke, sealed by graphite gland packing and metal bellows, stainless steel/graphite gaskets.

Applications:
Petrochemical plants, chemical plants, power stations, process engineering and general industry; for thermal oil, steam, toxic and volatile fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000901>

ECOLINE GLB 800



Class 150 - 800
NPS ½" - 2"
T [°C] 0 to +427

Description:
Globe valve to ANSI/ASME, with threaded sockets (NPT) or socket weld ends (SW), forged steel/stainless steel body, trim and bellows made of stainless steel, outside screw and yoke, sealed by graphite gland packing and metal bellows, stainless steel/graphite gaskets.

Applications:
Petrochemical plants, chemical plants, power stations, process engineering and general industry; for thermal oil, steam, toxic and volatile fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000902>

Globe valves to DIN/EN with gland packing

NORI 40 ZXL/ZXS



PN 25/40
DN 10 - 400
T [°C] -10 to +450

Description:

Globe valve to DIN/EN with flanged, butt weld or socket weld ends, with gland packing, with shut-off valve disc or throttling plug, rotating stem, seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000339>

NORI 40 ZXLF/ZXS F



PN 25/40
DN 10 - 200
T [°C] -10 to +450

Description:

Globe valve to DIN/EN with flanged, butt weld or socket weld ends, with gland packing, with shut-off valve disc or throttling plug, non-rotating stem, integrated position indicator, seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000341>

NORI 160 ZXL/ZXS



PN 63 - 160
DN 10 - 200
T [°C] -10 to +550

Description:

Globe valve to DIN/EN with flanged, butt weld or socket weld ends, with gland packing, with shut-off valve disc or throttling plug, rotating stem, seat/disc interface made of wear and corrosion resistant 17 % chrome steel or Stellite.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000343>

NORI 160 ZXL F/ZXS F



PN 63 - 160
DN 10 - 200
T [°C] -10 to +550

Description:

Globe valve to DIN/EN with flanged, butt weld or socket weld ends, with gland packing, with shut-off valve disc or throttling plug, non-rotating stem, integrated position indicator, seat/disc interface made of wear and corrosion resistant 17 % chrome steel or Stellite.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000345>

NORI 320 ZXS V



PN 250 - 320
DN 10 - 50
T [°C] -10 to +580

Description:

Globe valve to DIN/EN with flanged, butt weld or socket weld ends, gland packing, throttling plug, non-rotating stem, bayonet-type body/yoke joint, integrated position indicator, seat/disc interface made of Stellite.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000347>

NORI 500 ZXSV



| | |
|--------|-------------|
| PN | 250 - 500 |
| DN | 10 - 65 |
| T [°C] | -10 to +650 |

Description:
Globe valve to DIN/EN with butt weld or socket weld ends, gland packing, throttling plug, non-rotating stem, bayonet-type body/yoke joint, integrated position indicator, seat/disc interface made of Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000350>

BOACHEM-ZXA



| | |
|--------|-------------|
| PN | 10 - 40 |
| DN | 15 - 300 |
| T [°C] | -10 to +400 |

Description:
Globe valve to DIN/EN with flanged ends, body made of stainless steel, with gland packing, rotating stem, with shut-off valve disc or throttling plug.

Applications:
Process engineering, industry, building services, food and beverages industries, for aggressive fluids. Other fluids on request.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000354>

ECOLINE VA 16



| | |
|--------|-------------|
| PN | 16 |
| DN | 15 - 250 |
| T [°C] | -10 to +300 |

Description:
Globe valve to DIN/EN with flanged ends, body made of cast iron, with gland packing, rotating stem, with shut-off valve disc or throttling plug.

Applications:
District heating, domestic water supply, air-conditioning systems, cooling circuits, high-temperature hot water heating systems, water supply.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000673>

Globe valves to ANSI/ASME with gland packing

ECOLINE GLC 150-600



| | |
|--------|-----------|
| Class | 150 - 600 |
| NPS | 2" - 12" |
| T [°C] | 0 to +816 |

Description:
Globe valve to ANSI/ASME with flanged ends, cast steel A216 WCB, Trim 8 (Stellite/13 % chrome steel) for Class 150/300/600, Trim 5 (Stellite/Stellite) for Class 600, with bolted bonnet, outside screw and yoke, graphite gland packing, stainless steel/graphite gaskets.

Applications:
Refineries, power stations, process engineering and general industrial applications; water, steam, oil, gas. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000775>

ECOLINE GLF 150-600



| | |
|--------|-----------|
| Class | 150 - 600 |
| NPS | ½" - 2" |
| T [°C] | 0 to +816 |

Description:
Globe valve to ANSI/ASME with flanged ends, forged steel A105, Trim 8 (Stellite/13 % chrome steel), with bolted bonnet, outside screw and yoke, graphite gland packing, stainless steel/graphite gaskets, reduced bore.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000426>

ECOLINE GLF 800-2500



Class 800 - 2500
NPS ½" - 2"
T [°C] 0 to +538

Description:
Globe valve to ANSI/ASME with threaded sockets (NPT), butt weld ends (BW) or socket weld ends (SW), Trim 8 (Stellite/13 % chrome steel), with bolted bonnet (Class 800) or welded bonnet (Class 1500 and 2500), outside screw and yoke, graphite gland packing, stainless steel/graphite gaskets, available in carbon steel and alloy steel.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000796>

ECOLINE GLV 150-300



Class 150 - 300
NPS ½" - 12"
T [°C] 0 to +816

Description:
Globe valve to ANSI/ASME with flanged ends, cast steel A351 CF8/CF8M, Trim 2 (304/304) and Trim 10 (316/316) for Class 150/300, with bolted bonnet, outside screw and yoke, integral seat, graphite gland packing, stainless steel/graphite gaskets.

Applications:
Fine chemicals, food industry, general industry. For water, steam, gas and other fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000584>

SICCA 150-600 GLC



Class 150 - 600
NPS 2" - 10"
T [°C] 0 to +593

Description:
Globe valve to ANSI/ASME with flanged or butt weld ends, bolted bonnet, outside screw and yoke. Rotating, rising stem, seat/disc interface made of 13 % chrome steel, Stellite hard-faced; with graphite gasket and gland packing, available in carbon steel, low-alloy steel and stainless steel.

Applications:
Refineries, power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000484>

SICCA 900-2500 GLC



Class 900 - 2500
NPS 2" - 8"
T [°C] 0 to +650

Description:
Globe valve to ANSI/ASME with butt weld ends, Y-pattern, pressure seal design, outside screw and yoke, rising stem and non-rising handwheel, Stellite hard-faced seat/disc interface and back seat, with graphite gasket and gland packing. Available in carbon steel and alloy steel.

Applications:
Power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000485>

SICCA 800-4500 GLF



Class 800 - 4500
NPS ½" - 2"
T [°C] 0 to +650

Description:
Globe valve to ANSI/ASME with NPT (F) threaded ends or socket weld ends, bolted bonnet (Class 800) or welded bonnet (Class 1500/2500/4500), outside screw and yoke, Stellite hard-faced body seat, disc seating face made of Stellite hard-faced 13 % chrome steel, with graphite gasket and gland packing. Available in carbon steel and alloy steel.

Applications:
Refineries, power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000480>

WADA GL 150



| | |
|--------|--------------|
| Class | 150 |
| NPS | ½" - 12" |
| T [°C] | -196 to +100 |

Description:
Globe valve to ANSI/ASME with flanged, butt weld or socket weld ends, made of cast steel A351 CF3M/CF8/CF8M, bolted bonnet, outside screw and yoke, Stellite hard-faced valve disc and back seat, with graphite or PTFE gland packing, stainless steel/graphite gaskets.

Applications:
Natural gas liquefaction and other liquefied gases.



● e, m, p, h

<http://shop.ksb.com/catalog/k0/en/product/ES000901>

Globe valves for nuclear applications

NUCA/-A/-ES, Types I, II, IV



| | |
|------------------------|-----------|
| P _{max} [bar] | max. 320 |
| DN | 10 - 50 |
| T [°C] | max. +365 |

Description:
Globe valve for nuclear applications, with butt weld or socket weld ends, gland packing or bellows, replaceable seat (NUCA-ES), straight-way pattern, made of steel, stainless steel or nickel.

Applications:
Reactor cooling, moderator, safety feed, feed water, live steam and cleaning systems.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000452>

ZXNB



| | |
|------------------------|-----------|
| P _{max} [bar] | max. 210 |
| DN | 65 - 300 |
| T [°C] | max. +365 |

Description:
Bellows-type globe valve for nuclear applications, with butt weld ends, designed to meet safety-related requirements, in straight-way or angle pattern, or as two-way valve, made of steel or stainless steel.

Applications:
Reactor cooling, moderator, safety feed, feed water, live steam and cleaning systems.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000458>

ZXNVB



| | |
|------------------------|-----------|
| P _{max} [bar] | max. 210 |
| DN | 4 - 25 |
| T [°C] | max. +365 |

Description:
Globe valve for nuclear applications, with butt weld or socket weld ends, gland packing or bellows, straight-way pattern, made of steel or stainless steel.

Applications:
Reactor cooling, moderator, safety feed, feed water, live steam and cleaning systems.



● m

<http://shop.ksb.com/catalog/k0/en/product/ES000457>

ZYNB/ZYN



| | |
|------------------------|-----------|
| P _{max} [bar] | max. 62 |
| DN | 300 - 400 |
| T [°C] | max. +365 |

Description:
Globe valve for nuclear applications, with butt weld ends, designed to meet safety-related requirements, with gland packing or bellows, Y-valve, made of cast stainless steel.

Applications:
Residual heat removal systems in nuclear applications



● e

<http://shop.ksb.com/catalog/k0/en/product/ES000331>

Control systems to DIN/EN

BOA-Systronic



| | |
|--------|-------------|
| PN | 6/10/16 |
| DN | 20 - 200 |
| T [°C] | +20 to +120 |

Description:

Energy-saving system for the combined operation of pump and control valve. The system provides an all-in solution designed to access untapped hydraulic savings potential. Irrespective of the pump technology used, it allows savings of 50 % in pump electricity while also reducing primary energy costs thanks to lower return flow temperatures. The system can be combined with all control systems and pumps with a 0-10 V control input. Straightforward integration in automation systems with optional BACnet gateway.

Applications:

Supply temperature control in HVAC installations with volume flow rates of 0.5 to 185 m³/h and temperature differentials of 3 to 30 °K. Threaded (DN 20) or flanged (DN 25 to DN 200) line connections; suitable for upgrading installed systems and new systems, for connection to all types of heat generators (boiler systems or district heating), all main feed manifolds, all control systems, all supply temperatures.



<http://shop.ksb.com/catalog/k0/en/product/ES000494>

Automated globe valves to DIN/EN

BOA-H Mat E



| | |
|--------|-------------|
| PN | 16/25 |
| DN | 20 - 150 |
| T [°C] | -10 to +350 |

Description:

Automated globe valve to DIN/EN with flanged ends, with electric actuators and 3-point actuation, actuating forces from 2000 N to 14,000 N, stem sealed by maintenance-free PTFE V-packing (up to 250 °C) or graphite gland packing (up to 350 °C).

Applications:

General industrial facilities, process engineering, plant engineering, cooling circuits, heating systems.



e

<http://shop.ksb.com/catalog/k0/en/product/ES000801>

BOA-H Mat P



| | |
|--------|-------------|
| PN | 16/25 |
| DN | 20 - 150 |
| T [°C] | -10 to +350 |

Description:

Automated globe valve to DIN/EN with flanged ends, with pneumatic actuators in spring-to-open or spring-to-close design on option, actuating forces from 1500 N to 26,000 N, stem sealed by maintenance-free PTFE V-packing (up to 250 °C) or graphite gland packing (up to 350 °C).

Applications:

General industrial facilities, process engineering, plant engineering, cooling circuits, heating systems.



p

<http://shop.ksb.com/catalog/k0/en/product/ES000885>

Control valves to DIN/EN

BOA-CVE C/CS/W/IMS/EKB



| | |
|--------|-------------|
| PN | 6/10/16 |
| DN | 15 - 200 |
| T [°C] | -10 to +120 |

Description:

Control valve to DIN/EN based on standard type series BOA-Compact, BOA-SuperCompact, BOA-W, BOA-Compact EKB and BOA-Control IMS, bonnetless pressure-retaining body, soft-seated. Leakage rate selectable from 0.05 % to drop-tight at Kvs values between 6.3 and 700 m³/h and closing pressures of up to 16 bar. With intelligent microprocessor-controlled and pre-set electric actuators providing actuating forces from 1000 N to 14,000 N; electronic configuration of flow characteristic, Kvs value, control signal and actuating time using PC tool or manual parameterisation unit. Customised configuration can be implemented at the KSB factory on request.

Applications:

Hot-water heating systems up to 120 °C. Venting and air-conditioning systems. Water supply systems, drinking water. Not suitable for fluids containing mineral oils, steam or fluids liable to attack EPDM and uncoated cast iron. Other fluids on request.



e

<http://shop.ksb.com/catalog/k0/en/product/ES000326>

BOA-CVE H



| | |
|--------|-------------|
| PN | 16/25/40 |
| DN | 15 - 200 |
| T [°C] | -10 to +450 |

Description:

Service-friendly control valve to DIN/EN with flanged ends, either with linear or equal-percentage control characteristic at Kvs values of 0.1 to 630 m³/h and closing pressures of up to 40 bar; all internal parts are easy to replace without special tools, including the reversible seat; noise level reduced by standard two-stage pressure reduction combining a parabolic plug and multi-hole cage; with electric actuator.

Applications:

General industrial facilities, process engineering, plant engineering, cooling circuits, heating systems.



e

<http://shop.ksb.com/catalog/k0/en/product/ES000772>

BOA-CVP H



| | |
|--------|-------------|
| PN | 16/25/40 |
| DN | 15 - 200 |
| T [°C] | -10 to +450 |

Description:

Service-friendly control valve to DIN/EN with flanged ends, either with linear or equal-percentage control characteristic at Kvs values of 0.1 to 630 m³/h and closing pressures of up to 40 bar; all internal parts are easy to replace without special tools, including the reversible seat; noise level reduced by standard two-stage pressure reduction combining a parabolic plug and multi-hole cage; with pneumatic actuator.

Applications:

General industrial facilities, process engineering, plant engineering, cooling circuits, heating systems.






p




<http://shop.ksb.com/catalog/k0/en/product/ES000662>

Balancing and shut-off valves to DIN/EN

BOA-Control/BOA-Control IMS

| | | | | |
|---|--------|-------------|---|---|
|  | PN | 16 | Description: BOA-Control IMS: Balancing valve to DIN/EN with flanged ends, bonnetless, throttling plug, scaled position indicator, travel stop and insulating cap with anti-condensation feature, maintenance-free; full insulation possible; with ultrasonic sensor system for measuring flow rate and temperature, sensors not in contact with fluid handled, constant measurement accuracy when combined with BOATRONIC MS or BOATRONIC MS-420, independent of minimum differential pressures. BOA-Control: Balancing valve to DIN/EN with flanged ends, bonnetless, throttling plug, scaled position indicator, travel stop and insulating cap with anti-condensation feature, maintenance-free; full insulation possible; prepared for measuring flow rate with ultrasonic sensors and for temperature measurement, sensors not in contact with fluid handled, constant measurement accuracy when combined with BOATRONIC MS, independent of minimum differential pressures. Applications: Hot-water heating systems up to 120 °C. Cold water for air-conditioning systems. Not suitable for fluids containing mineral oils, steam or fluids liable to attack EPDM and uncoated cast iron. |  |
| | DN | 15 - 350 | | |
| | T [°C] | -10 to +120 | | |
|  | | | http://shop.ksb.com/catalog/k0/en/product/ES000323 | |

BOA-Control SAR

| | | | | |
|---|--------|-------------|--|--|
|  | PN | 16 | Description: Balancing valve to DIN/EN with female screwed ends; differential pressure measurement for flow metering with PFM 2000 measuring computer; digital travel position indicator with 40 settings, locking device and travel stop, maintenance-free. Applications: Hot-water heating systems up to 150 °C. Air-conditioning systems. Other fluids on request. |  |
| | DN | 10 - 50 | | |
| | T [°C] | -25 to +150 | | |
|  | | | http://shop.ksb.com/catalog/k0/en/product/ES000324 | |

Level control valves to DIN/EN

CONDA-VLC

| | | | | |
|---|--------|------------|---|---|
|  | PN | 16 | Description: Float valve to DIN/EN for controlling maximum and minimum liquid levels in tanks, with flanged ends (DN 40-300) or threaded ends (DN 25-32), body made of nodular cast iron; valve disc, stem, float and seat made of stainless steel. Applications: In water supply systems, industry and building services. For controlling water levels. |  |
| | DN | 25 - 300 | | |
| | T [°C] | -10 to +70 | | |
|  | | | http://shop.ksb.com/catalog/k0/en/product/ES000835 | |

Pressure reducing valves to DIN/EN

CONDA-VRC



| | |
|--------|-------------|
| PN | 16/25/40/64 |
| DN | 15 - 150 |
| T [°C] | -10 to +70 |

Description:
Direct-acting pressure reducing valve to DIN/EN with flanged ends (DN 50-150) or threaded ends (DN 15-50), body made of nodular cast iron; valve disc, stem and seat made of stainless steel.

Applications:
In water supply systems for controlling downstream pressure, in fire-fighting systems for reducing excess pressure caused by pumps, in irrigation system as an efficient protection against water hammer, in industry and building services.



<http://shop.ksb.com/catalog/k0/en/product/ES000834>

Pressure sustaining valves to DIN/EN

CONDA-VSM



| | |
|--------|------------|
| PN | 16/25/40 |
| DN | 50 - 150 |
| T [°C] | -10 to +70 |

Description:
Direct-acting pressure sustaining valve to DIN/EN with flanged ends, body made of nodular cast iron, valve disc, stem and seat made of stainless steel.

Applications:
In water supply systems for controlling upstream pressure, in irrigation or fire-fighting systems, industry and building services.



<http://shop.ksb.com/catalog/k0/en/product/ES000678>

Air valves to DIN/EN

BOAVENT-AVF



| | |
|--------|-------------|
| PN | 16 |
| DN | 50 - 300 |
| T [°C] | -10 to +120 |

Description:
Automatic air valve with two floats and three functions. Flanged ends, body made of nodular cast iron, double-chamber design with ABS floats. The air valve ensures proper operation of the piping system, allowing the entry and discharge of large volumes of air and release of air pockets in working conditions.

Applications:
Water supply system, clean water, irrigation.



<http://shop.ksb.com/catalog/k0/en/product/ES000831>

BOAVENT-SIF



| | |
|--------|------------|
| PN | 16 |
| DN | 25 - 200 |
| T [°C] | -10 to +70 |

Description:
Automatic air valve with one float and three functions. With flanged ends (DN 25-300R) or threaded ends (DN 25-150), body made of stainless steel, single-chamber design with polypropylene float. The air valve ensures proper operation of the piping system, allowing the entry and discharge of large volumes of air and release of air pockets in working conditions.

Applications:
Water supply system, clean water, irrigation.



<http://shop.ksb.com/catalog/k0/en/product/ES000832>

BOAVENT-SVA



PN 16
DN 50 - 200
T [°C] -10 to +70

Description:
Automatic air valve with one float and three functions. With flanged or threaded ends, body made of nodular cast iron, single-chamber design with polypropylene float. The air valve ensures proper operation of the piping system, allowing the entry and discharge of large volumes of air and release of air pockets in working conditions.

Applications:
Water supply, waste water, untreated waste water.



<http://shop.ksb.com/catalog/k0/en/product/ES000833>

BOAVENT-SVF



PN 16/25/40
DN 25 - 300
T [°C] -10 to +70

Description:
Automatic air valve with one float and three functions. With flanged ends (DN 25-300R) or threaded ends (DN 25-150), body made of nodular cast iron (PN 16-40) or carbon steel (PN 64), single-chamber design with polypropylene float. The air valve ensures proper operation of the piping system, allowing the entry and discharge of large volumes of air and release of air pockets in working conditions.

Applications:
Water supply system, clean water, irrigation.



<http://shop.ksb.com/catalog/k0/en/product/ES000832>

Vent valves for nuclear applications

SISTO-VentNA



PN 16
DN 15
T [°C] max. +100

Description:
Vent valve for nuclear applications, with butt weld ends, soft-seated.

Applications:
Heating systems, air-conditioning systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000842>

SISTO-KRVNA



PN 16
DN 25 - 100
T [°C] max. +100

Description:
Vent valve for nuclear applications, with flanged or butt weld ends, soft-seated, with floating ball.

Applications:
Tank venting, drainage systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000839>

Gate valves to DIN/EN

COBRA-SGP/SGO/SGF



PN 16/25
DN 25 - 600
T [°C] -10 to +70

Description:
Gate valve to DIN/EN with flanged ends, elastomer-coated wedge, bolted bonnet, rotating stem, inside screw, body made of nodular cast iron.

Applications:
Water supply and treatment systems, air-conditioning systems.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000828>

COBRA-SMP



PN 16
DN 40 - 300
T [°C] -10 to +110

Description:
Gate valve to DIN/EN with flanged ends, bolted bonnet, metal-seated, rotating stem, inside screw, body and flexible wedge made of nodular cast iron, stem and seats made of stainless steel.

Applications:
Water supply systems, heating systems, air-conditioning systems, general industry, building services.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000829>

ECOLINE SP/SO



PN 10/16/25
DN 40 - 600
T [°C] -10 to +110

Description:
Gate valve to DIN/EN with flanged ends, bolted bonnet, metal-seated, rotating stem, inside screw, body made of cast iron, seats made of brass.

Applications:
Water supply systems, heating systems, air-conditioning systems, general industry, water engineering, building services.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000654>

ECOLINE GT 40



PN 10 - 40
DN 50 - 600
T [°C] -10 to +400

Description:
Gate valve to DIN/EN with flanged ends or butt weld ends, bolted bonnet, body made of cast steel, non-rotating stem, with flexible wedge, seat/disc interface made of wear and corrosion resistant 13 % chrome steel or Stellite.

Applications:
In industrial plants, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000676>

STAAL 40 AKD/AKDS



PN 10 - 40
DN 50 - 600
T [°C] -10 to +450

Description:
Gate valve to DIN/EN with flanged or butt weld ends, bolted bonnet, body of forged or welded steel construction, non-rotating stem, split wedge with flexibly mounted discs for precise alignment with the body seats. Seat/disc interface made of wear and corrosion resistant 17 % chrome steel.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000469>

STAAL 100 AKD/AKDS



| | |
|--------|-------------|
| PN | 63 - 100 |
| DN | 50 - 500 |
| T [°C] | -10 to +530 |

Description:
Gate valve to DIN/EN with flanged or butt weld ends, bolted bonnet, body of forged or welded steel construction, non-rotating stem, split wedge with flexibly mounted discs for precise alignment with the body seats. Seat/disc interface made of wear and corrosion resistant 17 % chrome steel or Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000369>

AKG-A/AKGS-A



| | |
|--------|-------------|
| PN | 63 - 160 |
| DN | 80 - 300 |
| T [°C] | -10 to +550 |

Description:
Gate valve to DIN/EN with flanged or butt weld ends, pressure seal design, body of forged or welded construction, non-rotating stem, split wedge with flexibly mounted discs for precise alignment with the body seats. Seat/disc interface made of wear and corrosion resistant 17 % chrome steel or Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000371>

ZTS



| | |
|--------|-----------------|
| PN | Approx. 600 bar |
| Class | 4500 |
| DN | 50 - 800 |
| NPS | 2" - 32" |
| T [°C] | -10 to +650 |

Description:
Gate valve to DIN/EN or ANSI/ASME, with butt weld ends, pressure seal design, billet-forged body, seat/disc interface made of wear and corrosion resistant Stellite, split wedge with flexibly mounted discs for precise alignment with the body seats.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000375>

Gate valves to ANSI/ASME

ECOLINE GTB 800



| | |
|--------|-----------|
| Class | 150-800 |
| NPS | ½" - 2" |
| T [°C] | 0 to +427 |

Description:
Gate valve to ANSI/ASME, with threaded sockets (NPT) or socket weld ends (SW), forged steel/stainless steel body, trim and bellows made of stainless steel, with bolted bonnet, outside screw and yoke, sealed by graphite gland packing and metal bellows, stainless steel/graphite gaskets.

Applications:
Petrochemical plants, chemical plants, power stations, process engineering and general industry; for thermal oil, steam, toxic and volatile fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000903>

ECOLINE GTC 150-600



| | |
|--------|-----------|
| Class | 150 - 600 |
| NPS | 2" - 36" |
| T [°C] | 0 to +816 |

Description:
Gate valve to ANSI/ASME with flanged ends, cast steel A216 WCB, Trim 8 (Stellite/13 % chrome steel) for Class 150/300/600, Trim 5 (Stellite/Stellite) for Class 600, with bolted bonnet, outside screw and yoke, non-rotating stem, flexible wedge, graphite gland packing, stainless steel/graphite gaskets.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000774>

ECOLINE GTF 150-600



Class 150 - 600
NPS ½" - 2"
T [°C] 0 to +816

Description:
Gate valve to ANSI/ASME with flanged ends, forged steel A105, Trim 8 (Stellite/13 % chrome steel), with bolted bonnet, outside screw and yoke, non-rotating stem, single-piece wedge, graphite gland packing, stainless steel/graphite gaskets, reduced bore.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; water, steam, gas, oil and other non-aggressive fluids.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000611>

ECOLINE GTF 800-2500



Class 800 - 2500
NPS ½" - 2"
T [°C] 0 to +538

Description:
Gate valve to ANSI/ASME with threaded sockets (NPT), butt weld ends (BW) or socket weld ends (SW), Trim 8 (Stellite/13 % chrome steel), with bolted bonnet (Class 800) or welded bonnet (Class 1500 and 2500), outside screw and yoke, single-piece wedge, graphite gland packing, stainless steel/graphite gaskets, available in carbon steel and alloy steel.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; water, steam, gas, oil and other non-aggressive fluids.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000797>

ECOLINE GTV 150-300



Class 150 - 300
NPS ½" - 12"
T [°C] 0 to +816

Description:
Gate valve to ANSI/ASME with flanged ends, cast steel A351 CF8/CF8M, Trim 2 (304/304) and Trim 10 (316/316) for Class 150/300, with bolted bonnet, outside screw and yoke, non-rotating stem, flexible wedge, integral seat, graphite gland packing, stainless steel/graphite gaskets.

Applications:
Fine chemicals, food industry, general industry; water, steam, gas and other fluids.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000373>

SICCA 150-600 GTC



Class 150 - 600
NPS 2" - 24"
T [°C] 0 to +593

Description:
Gate valve to ANSI/ASME with flanged or butt weld ends, bolted bonnet, outside screw and yoke, flexible wedge, non-rotating rising stem and non-rising handwheel, seat/disc interface made of 13 % chrome steel, Stellite hard-faced; with graphite gasket and gland packing, available in carbon steel, low-alloy steel and stainless steel.

Applications:
Power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000482>

SICCA 900-3600 GTC



Class 900 - 3600
NPS 2" - 28"
T [°C] 0 to +650

Description:
Gate valve to ANSI/ASME with butt weld ends, pressure seal design, split-wedge design, outside screw and yoke, rising stem and non-rising handwheel, Stellite hard-faced seat/disc interface and back seat, with graphite gasket and gland packing. Available in carbon steel and alloy steel.

Applications:
Power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



● e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000483>

SICCA 800-1500 GTF



Class
NPS
T [°C]

800 - 4500
½" - 2"
0 to +593

Description:

Gate valve to ANSI/ASME with NPT (F) threaded ends or socket weld ends, bolted bonnet (Class 800) or welded bonnet (Class 1500), single-piece wedge, outside screw and yoke, seat/disc interface made of 13 % chrome steel, Stellite hard-faced, with graphite gasket and gland packing. Available in carbon steel and alloy steel.

Applications:

Refineries, power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



e, m

<http://shop.ksb.com/catalog/k0/en/product/ES000479>

WADA GT 150



Class
NPS
T [°C]

150
1" - 12"
-196 to +100

Description:

Gate valve to ANSI/ASME with flanged, butt weld or socket weld ends, made of cast steel A351 CF3M/CF8/CF8M, bolted bonnet, outside screw and yoke, flexible wedge, graphite or PTFE gland packing, stainless steel/graphite gaskets.

Applications:

Natural gas liquefaction and other liquefied gases.



e, m, p, h

<http://shop.ksb.com/catalog/k0/en/product/ES000888>

Gate valves for nuclear applications

ZTN



P_{max} [bar]
DN
T [°C]

max. 320
80 - 700
max. +365

Description:

Gate valve for nuclear applications, with butt weld ends, bolted or pressure seal bonnet, forged or welded body, non-rotating stem, in split-wedge or parallel-disc design, made of steel or stainless steel.

Applications:

Reactor cooling, safety feed, feed water, live steam, cleaning and condensate systems.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000456>

Body pressure relief valves

UGS



PN
DN

max. 750 bar
15

Description:

Spring-loaded body pressure relief valve to DIN/EN, with or without bursting disc, for gate valves in pressure seal design.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000899>

Knife gate valves to DIN/EN

HERA-BD



| | |
|--------|-------------|
| PN | 10 |
| DN | 50 - 1200 |
| T [°C] | -10 to +120 |

Description:

Knife gate valve to DIN/EN with wafer-type single-piece or two-piece body made of grey cast iron, bi-directional, with gland packing, non-rising stem, corrosion-protected by epoxy coating.

Applications:

In industrial plants, waste water and process engineering, food industry. For water, waste water and solids-laden fluids. Other fluids on request.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000597>

Knife gate valves to ANSI/ASME

HERA-BDS



| | |
|--------|-------------|
| Class | 150 |
| DN | 50 - 600 |
| T [°C] | -10 to +120 |

Description:

Knife gate valve to ANSI/ASME with full-lug body made of carbon steel or stainless steel; bi-directional, with gland packing, rubber-lined, rising stem, non-rising handwheel.

Applications:

Primarily in mining for handling slurries, abrasive fluids and high-density fluids; also in pulp applications, cement plants, sewage treatment plants and the chemical industry. Other fluids on request.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000895>

HERA-BHT



| | |
|--------|-------------|
| Class | 150 |
| DN | 80 - 600 |
| T [°C] | -10 to +100 |

Description:

Knife gate valve to ANSI/ASME, semi-lug body made of carbon steel or stainless steel, two-piece body, bi-directional, with gland packing, through-going blade, rising stem, non-rising handwheel, robust yoke for actuator mounting as standard.

Applications:

Primarily in mining for handling slurries and high-density fluids; excellent flow characteristic due to through-going blade; also in pulp applications and water applications. Other fluids on request.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000891>

HERA-SH



| | |
|--------|-------------|
| Class | 150 |
| DN | 50 - 1000 |
| T [°C] | -10 to +180 |

Description:

Knife gate valve to ANSI/ASME with full-lug body made of carbon steel or stainless steel, single-piece body, uni-directional, with gland packing, rising stem, non-rising handwheel.

Applications:

In industrial and waste water engineering, pulp and paper industry, food and beverages industry, chemical industry. For water, waste water and solids-laden fluids. Other fluids on request.





● e, m, p



<http://shop.ksb.com/catalog/k0/en/product/ES000844>

Lift check valves to DIN/EN



BOA-RPL

| | | | | |
|---|--------------|------------------------|---|---|
|  | PN | 10/16 | Description: Ball check valve to DIN/EN with flanged or female/female-threaded ends, made of nodular cast iron, NBR-coated ball, bolted cover, suitable for installation in vertical or horizontal pipes. Applications: Water supply and treatment systems, waste water. |  |
| | DN T [°C] | 25 - 400 -10 to +70 | | |
| http://shop.ksb.com/catalog/k0/en/product/ES000635 | | | | |



BOA-RFV

| | | | | |
|---|--------------|------------------------|--|---|
|  | PN | 10/16/25/40/64 | Description: Lift check valve to DIN/EN with flanged ends, Venturi-type body, max. flow velocity 2.5 m/s. Body made of cast iron, check disc made of brass and cast iron, seat made of stainless steel. Suitable for installation in horizontal and vertical pipes. Rapid closure without surge pressures. Applications: Water supply systems, heating systems, air-conditioning systems. |  |
| | DN T [°C] | 40 - 600 -10 to +90 | | |
| http://shop.ksb.com/catalog/k0/en/product/ES000653 | | | | |



BOA-RVK

| | | | | |
|---|--------------|-------------------------|--|---|
|  | PN | 6/10/16 | Description: Lift check valve to DIN/EN with wafer-type body, centring aided by the body shape, shut-off by spring-loaded plate or valve disc guided by three stainless steel guiding pins. Low-noise designs with plastic plate (DN 15-100) or valve disc with O-ring (DN 125-200), maintenance-free. Applications: Industrial plants and heating systems, liquids and gases, hot-water heating systems, high-temperature hot water heating systems, heat transfer systems. Any limits given in the technical codes must be complied with. Not suitable for fluids liable to attack the materials used. Other fluids on request. |  |
| | DN T [°C] | 15 - 200 -20 to +250 | | |
| http://shop.ksb.com/catalog/k0/en/product/ES000357 | | | | |

BOA-R

| | | | | |
|---|--------------|-------------------------|--|---|
|  | PN | 6/16 | Description: Lift check valve to DIN/EN with flanged ends, spring-loaded valve disc, maintenance-free. Applications: Hot-water heating systems, high-temperature hot water heating systems, heat transfer systems. General steam applications in building services and industry. Other fluids on request. |  |
| | DN T [°C] | 15 - 350 -10 to +350 | | |
| http://shop.ksb.com/catalog/k0/en/product/ES000356 | | | | |

NORI 40 RXL/RXS

| | | | | |
|---|--------------|-------------------------|--|---|
|  | PN | 25/40 | Description: Lift check valve to DIN/EN, with flanged, butt weld or socket weld ends, check disc with closing spring, seat/disc interface made of wear and corrosion resistant chrome steel or chrome nickel steel. Applications: In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request. |  |
| | DN T [°C] | 10 - 300 -10 to +450 | | |
| http://shop.ksb.com/catalog/k0/en/product/ES000358 | | | | |

NORI 160 RXL/RXS



| | |
|--------|-------------|
| PN | 63 - 160 |
| DN | 10 - 200 |
| T [°C] | -10 to +550 |

Description:
Lift check valve to DIN/EN, with flanged, butt weld or socket weld ends, check disc with closing spring, seat/disc interface made of wear and corrosion resistant 17 % chrome steel or Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000360>

RGS



| | |
|--------|-------------|
| PN | 250 - 500 |
| DN | 10 - 50 |
| T [°C] | -10 to +580 |

Description:
Lift check valve to DIN/EN, with butt weld or socket weld ends, Y-pattern, check disc with closing spring, pressure seal design, Hastelloy-faced body seats.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000364>

BOACHEM-RXA



| | |
|--------|-------------|
| PN | 10 - 40 |
| DN | 15 - 300 |
| T [°C] | -10 to +400 |

Description:
Lift check valve to DIN/EN with flanged ends, body made of stainless steel, check disc with closing spring, lapped seat/disc interface.

Applications:
Process engineering, industry, building services, food and beverages industries, for aggressive fluids. Other fluids on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000366>

Lift check valves to ANSI/ASME

ECOLINE PTF 150-600



| | |
|--------|-----------|
| Class | 150 - 600 |
| NPS | ½" - 2" |
| T [°C] | 0 to +816 |

Description:
Lift check valve to ANSI/ASME with flanged ends, forged steel A105, Trim 8 (Stellite/13 % chrome steel), reduced bore, with bolted cover, spring-loaded valve disc.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



<http://shop.ksb.com/catalog/k0/en/product/ES000424>

ECOLINE PTF 800-2500



| | |
|--------|------------|
| Class | 800 - 2500 |
| NPS | ½" - 2" |
| T [°C] | 0 to +538 |

Description:
Lift check valve to ANSI/ASME with threaded sockets (NPT), butt weld ends (BW) or socket weld ends (SW), Trim 8 (Stellite/13 % chrome steel), with bolted cover (Class 800) or welded cover (Class 1500 and 2500), spring-loaded valve disc, available in carbon steel and alloy steel.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



<http://shop.ksb.com/catalog/k0/en/product/ES000374>

SICCA 800-4500 PCF



Class
NPS
T [°C]

800 - 4500
½" - 2"
0 to +650

Description:

Lift check valve to ANSI/ASME with NPT (F) threaded ends or socket weld ends, with spring-loaded valve disc, bolted cover (Class 800) or welded cover (Class 1500/2500/4500), Stellite hard-faced body seat, disc seating face made of Stellite hard-faced 13 % chrome steel, with graphite gasket. Available in carbon steel and alloy steel.

Applications:

Refineries, power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000481>

WADA SC 150



Class
NPS
T [°C]

150
½" - 18"
-196 to +100

Description:

Swing check valve / lift check valve to ANSI/ASME with flanged, butt weld or socket weld ends, made of cast steel A351 CF3M/CF8/CF8M, bolted cover, dash-pot function, graphite or stainless steel/graphite gaskets.

Applications:

Natural gas liquefaction and other liquefied gases.



<http://shop.ksb.com/catalog/k0/en/product/ES000890>

Lift check valves for nuclear applications

NUCA/-A/-ES, Type V



P_{max} [bar]
DN
T [°C]

max. 410
10 - 50
max. +365

Description:

Lift check valve for nuclear applications, with butt weld ends, replaceable seat (NUCA-ES), straight-way pattern, made of steel or stainless steel.


Applications:

Feed water and live steam systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000455>

RJN



P_{max} [bar]
DN
T [°C]

max. 140
80 - 600
max. +300

Description:

Damped lift check valve for nuclear applications, with butt weld ends, individually selectable damping characteristic, made of steel or stainless steel.

Applications:

Feed water and live steam systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000459>

RYN



P_{max} [bar]
DN
T [°C]

max. 210
65 - 300
max. +365

Description:

Combined lift check/shut-off valve for nuclear applications, with butt weld ends, Y-pattern, with gland packing or bellows, made of steel or stainless steel.

Applications:

Feed water and live steam systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000333>

Swing check valves to DIN/EN

COBRA-SCBS



| | |
|--------|-------------|
| PN | 16 |
| DN | 50 - 300 |
| T [°C] | -10 to +300 |

Description:
Swing check valve to British standards, with flanged ends, metal-seated, body and valve disc made of nodular cast iron, with bolted cover, stainless steel/graphite gaskets.

Applications:
Water supply, treatment and distribution systems, waste water, irrigation, drinking water, seawater, air, gas, oil.



<http://shop.ksb.com/catalog/k0/en/product/ES000827>

ECOLINE WT/WTI



| | |
|--------|-------------|
| PN | 16 |
| DN | 50 - 300 |
| T [°C] | -10 to +110 |

Description:
Swing check valve to DIN/EN with wafer-type body; body and valve disc made of carbon steel (WT) or stainless steel (WTI), O-ring made of Viton.

Applications:
Irrigation systems, district heating, domestic water supply, sewage treatment plants, air-conditioning systems, cooling circuits, water supply systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000638>

STAAL 40 AKK/AKKS



| | |
|--------|-------------|
| PN | 10 - 40 |
| DN | 80 - 400 |
| T [°C] | -10 to +450 |

Description:
Swing check valve to DIN/EN with flanged or butt weld ends, bolted cover, internally mounted hinge pin, body of welded steel construction, seat/disc interface made of wear and corrosion resistant 17 % chrome steel.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000471>

STAAL 100 AKK/AKKS



| | |
|--------|-------------|
| PN | 63 - 100 |
| DN | 80 - 400 |
| T [°C] | -10 to +530 |

Description:
Swing check valve to DIN/EN with flanged or butt weld ends, bolted cover, internally mounted hinge pin, body of forged or welded steel construction, seat/disc interface made of wear and corrosion resistant 17 % chrome steel or Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000391>

AKR/AKRS



| | |
|--------|-------------|
| PN | 63 - 160 |
| DN | 80 - 300 |
| T [°C] | -10 to +550 |

Description:
Swing check valve to DIN/EN with flanged or butt weld ends, pressure seal design, internally mounted hinge pin, body of forged and welded construction, seat/disc interface made of wear and corrosion resistant 17% chrome steel or Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000394>

ZRS



| | |
|--------|-----------------|
| PN | Approx. 600 bar |
| DN | 50 - 800 |
| T [°C] | -10 to +650 |

Description:
Swing check valve to DIN/EN, with butt weld ends, pressure seal design, internally mounted hinge pin, billet-forged body; seat/disc interface made of wear and corrosion resistant Stellite.

Applications:
In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000396>

SISTO-RSK/RSKS



| | |
|--------|-------------|
| PN | 16 |
| DN | 25 - 300 |
| T [°C] | -20 to +140 |

Description:
Swing check valve to DIN/EN with flanged ends, body with or without lining, soft-seated, no dead volumes, straight-way pattern, full bore, slanted seat, static sealing to atmosphere; with soft rubber encapsulated pre-loaded valve disc featuring short travel to closure.

Applications:
In building services, industrial plants and power stations; suitable for drinking water, service water, from fluids handled in the food and beverages industry to abrasive and aggressive products in chemical and process engineering.



<http://shop.ksb.com/catalog/k0/en/product/ES000397>

SERIE 2000



| | |
|--------|--------------|
| PN | 16/25 |
| Class | 150/300 |
| DN | 50 - 600 |
| T [°C] | -196 to +538 |

Description:
Dual-plate check valve with single-piece, wafer-type body made of lamellar graphite cast iron, nodular cast iron, steel, stainless steel or copper aluminium alloy, metal/elastomer-seated or metal/metal-seated, maintenance-free, connections to EN, ASME or JIS.

Applications:
Building services: heating, air-conditioning, water supply, irrigation, water treatment. General processes: water, air, gas. Process engineering, chemical and petrochemical industry, sugar industry, paper industry, water supply, desalination, marine applications: water, air, gas, hydrocarbons.



<http://shop.ksb.com/catalog/k0/en/product/ES000393>

Swing check valves to ANSI/ASME

ECOLINE SCC 150-600



| | |
|--------|-----------|
| Class | 150 - 600 |
| NPS | 2" - 24" |
| T [°C] | 0 to +816 |

Description:
Swing check valve to ANSI/ASME with flanged ends, cast steel A216 WCB, Trim 8 (Stellite/13 % chrome steel) for Class 150/300/600, Trim 5 (Stellite/Stellite) for Class 600, with bolted cover, internally mounted hinge pin (2" - 12"), stainless steel/graphite gaskets.

Applications:
Refineries, power stations, process engineering and general industry; water, steam, oil, gas. Other applications on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000776>

ECOLINE SCF 150-600



Class 150 - 600
NPS ½" - 2"
T [°C] 0 to +816

Description:
Swing check valve to ANSI/ASME with flanged ends, forged steel A105, Trim 8 (Stellite/13 % chrome steel), reduced bore, with bolted cover, internally mounted hinge pin.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



<http://shop.ksb.com/catalog/k0/en/product/ES000799>

ECOLINE SCF 800-2500



Class 800 - 2500
NPS ½" - 2"
T [°C] 0 to +538

Description:
Swing check valve to ANSI/ASME with threaded sockets (NPT), butt weld ends (BW) or socket weld ends (SW), Trim 8 (Stellite/13 % chrome steel), with bolted cover (Class 800) or welded cover (Class 1500 and 2500), internally mounted hinge pin, available in carbon steel and alloy steel.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



<http://shop.ksb.com/catalog/k0/en/product/ES000798>

ECOLINE SCV 150-300



Class 150 - 300
NPS ½" - 12"
T [°C] 0 to +816

Description:
Swing check valve to ANSI/ASME with flanged ends, cast steel A351 CF8/CF8M, Trim 2 (304/304) and Trim 10 (316/316) for Class 150/300, with bolted cover, integral seat, stainless steel/graphite gaskets.

Applications:
Fine chemicals, food industry and general industry. For water, steam, gas and other fluids. Other applications on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000335>

SICCA 150-600 SCC



Class 150 - 600
NPS 2" - 24"
T [°C] 0 to +593

Description:
Swing check valve to ANSI/ASME with flanged or butt weld ends, bolted cover, internally mounted hinge pin. Bigger sizes with anti-slam/dash pot arrangement (optional), graphite gasket. Seat/disc interface made of 13 % chrome steel, Stellite hard-faced. Available in carbon steel, low-alloy steel and stainless steel.

Applications:
Power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000486>

SICCA 900-3600 SCC



Class 900 - 3600
NPS 2" - 28"
T [°C] 0 to +650

Description:
Swing check valve to ANSI/ASME with butt weld ends, pressure seal design, internally mounted hinge pin, Stellite hard-faced seat/disc interface, with graphite gasket. Available in carbon steel and alloy steel.

Applications:
Power stations, general industry and process engineering. For water, steam, oil, gas and non-aggressive fluids. Other applications on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000487>

WADA SC 150



Class 150
NPS ½" - 18"
T [°C] -196 to +100

Description:
Swing check valve / lift check valve to ANSI/ASME with flanged, butt weld or socket weld ends, made of cast steel A351 CF3M/CF8/CF8M, bolted cover, dash-pot function, graphite or stainless steel/graphite gaskets.
Applications:
Natural gas liquefaction and other liquefied gases.



<http://shop.ksb.com/catalog/k0/en/product/ES000890>

Swing check valves for nuclear applications

SISTO-RSKNA



PN 16
DN 25 - 300
T [°C] max. +100

Description:
Swing check valve with flanged ends, body with or without lining, soft-seated, no dead volumes, straight-way pattern, full bore, slanted seat, static sealing to atmosphere; with soft rubber encapsulated pre-loaded valve disc featuring short travel to closure.
Applications:
Waste water systems, pump systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000838>

ZRN



P_{max} [bar] max. 320
DN 50 - 600
T [°C] max. +365

Description:
Swing check valve for nuclear applications, with butt weld ends, bolted cover, internally mounted hinge pin, forged body made of steel or stainless steel.
Applications:
Safety feed, feed water, live steam and condensate systems.



<http://shop.ksb.com/catalog/k0/en/product/ES000399>

Tilting disc check valves to DIN/EN

COBRA-TDC01/03



PN 10/16/25
DN 100 - 2200
T [°C] -10 to +70

Description:
Tilting disc check valve to DIN/EN with flanged ends, with lever and counterweight/hydraulic damper, body and valve disc made of nodular cast iron, body seats made of stainless steel.
Applications:
Water supply systems



<http://shop.ksb.com/catalog/k0/en/product/ES000830>

Strainers to DIN/EN

BOA-S



PN 6/16/25
DN 15 - 400
T [°C] -10 to +350

Description:
Strainer to DIN/EN with flanged ends, with standard or fine screen; all nominal sizes with drain plug in the cover.

Applications:
Hot-water heating systems, high-temperature hot water heating systems, heat transfer systems. General steam applications in building services and industry. Other fluids on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000401>

NORI 40 FSL/FSS



PN 25/40
DN 15 - 300
T [°C] -10 to +450

Description:
Strainer to DIN/EN with flanged or butt weld ends, body made of cast steel, with standard or fine screen; all nominal sizes with drain plug in the cover, optional magnetic inserts.

Applications:
In heat transfer systems, industrial plants, building services and shipbuilding. For thermal oils, water, steam, gas and other non-aggressive fluids. Other fluids on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000523>

BOACHEM-FSA



PN 10 - 40
DN 15 - 400
T [°C] -10 to +400

Description:
Strainer to DIN/EN with flanged ends, body made of stainless steel, with standard or fine screen; all nominal sizes with drain plug in the cover.

Applications:
Process engineering, industry, building services, food and beverages industries, for aggressive fluids. Other fluids on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000402>

Strainers to ANSI/ASME

ECOLINE FYC 150-600



Class 150 - 600
NPS 2" - 12"
T [°C] 0 to +816

Description:
Strainer to ANSI/ASME with flanged ends, Y-pattern, bolted cover, cast steel A216 WCB, screen made of stainless steel 304, mesh width 1.5 mm.

Applications:
Refineries, power stations, process engineering and general industrial applications; water, steam, gas, oil. Other applications on request.



<http://shop.ksb.com/catalog/k0/en/product/ES000665>

ECOLINE FYF 800



Class 800
NPS ½" - 2"
T [°C] 0 to +816

Description:
Strainer to ANSI/ASME with threaded sockets (NPT) or socket weld ends (SW), Y-pattern, with bolted cover, forged steel A105, screen made of stainless steel 304. Mesh width 0.8 to 0.9 mm.

Applications:
Industrial applications, power stations, process engineering, refineries, oil and marine applications; for water, steam, gas, oil and other non-aggressive fluids.



<http://shop.ksb.com/catalog/k0/en/product/ES000666>

Centred-disc butterfly valves

BOAX-CBV13



PN 10/16
DN 500 - 1200
T [°C] -10 to +115

Description:
Centred-disc butterfly valve with epoxy coating. Perfect shut-off in either flow direction. Flanged ends to EN standards, body made of nodular cast iron, valve disc made of stainless steel.

Applications:
Shut-off or control duties, drinking water, seawater, water supply, treatment and distribution systems, waste water, irrigation, ultra-pure water, air, oil.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000825>

BOAX-S/SF



PN [bar] 6/10/16
DN 20 - 600
T [°C] -10 to +130

Description:
Centred-disc butterfly valve for building services, with heat barrier and elastomer liner (EPDM XU or Nitrile K), with lever, manual gearbox or electric actuator; semi-lug body (T2) or full-lug body (T4) suitable for downstream dismantling and dead-end service. Valve disc made of stainless steel 1.4308, connections to EN.

Applications:
Heating, ventilation, air-conditioning systems, for drinking water.



e, m, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000388>

BOAX-S/SF Gaz



PN [bar] max. 10
DN 20 - 600
T [°C] -20 to +60

Description:
Centred-disc butterfly valve for gas lines, with elastomer liner (epichlorohydrin EG), with yellow lever; semi-lug body (T2), full-lug body (T4). Valve disc made of stainless steel 1.4308, connections to EN.

Applications:
Gas lines



m

<http://shop.ksb.com/catalog/k0/en/product/ES000388>

BOAX-B



| | |
|----------|-------------|
| PN [bar] | 10/16 |
| DN | 40 - 1000 |
| T [°C] | -10 to +130 |

Description:
Centred-disc butterfly valve, sealed by elastomer liner (EPDM XC or Nitrile K), with lever, manual gearbox, pneumatic or electric actuator; wafer-type body (T1), semi-lug body (T2), full-lug body (T4) or U-section body with flat faces (T5). Body types T2, T4 and T5 are suitable for downstream dismantling and dead-end service. Valve disc made of nodular cast iron or stainless steel. Connections to EN, ASME or JIS.

Applications:

Engineering contractors. General water circuits, heating oil, oil. Shut-off and control duties in water management for water supply, water treatment, drainage and irrigation.



e, m, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000573>

BOAX-B Gaz



| | |
|----------|------------|
| PN [bar] | 10/16 |
| DN | 40 - 300 |
| T [°C] | -20 to +90 |

Description:
Centred-disc butterfly valve, sealed by elastomer liner (epichlorohydrin EG or Nitrile K), with lever; semi-lug body (T2) or full-lug body (T4), valve disc made of nodular cast iron. Connections to EN.

Applications:

Gas pipes to NF ROB.GAZ N°095.00



m

<http://shop.ksb.com/catalog/k0/en/product/ES000574>

BOAX-B APSAD



| | |
|----------|-------------|
| PN [bar] | max. 16 |
| DN | 40 - 300 |
| T [°C] | -10 to +110 |

Description:
Centred-disc butterfly valve, sealed by elastomer liner (EPDM XC), with manual gearbox to APSAD; semi-lug body (T2) suitable for downstream dismantling, valve disc made of nodular cast iron. Connections to EN.

Applications:

Fire protection



m

<http://shop.ksb.com/catalog/k0/en/product/ES000867>

BOAX-B DVGW



| | |
|----------|------------|
| PN [bar] | 10/16 |
| DN | 40 - 300 |
| T [°C] | -20 to +60 |

Description:
Centred-disc butterfly valve, sealed by elastomer liner (epichlorohydrin), with lever; semi-lug body (T2) or full-lug body (T4), valve disc made of nodular cast iron or stainless steel. Connections to EN.

Applications:

Gas lines and biogas plants.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000574>

BOAX-B FM



PN [bar] 16
DN 40 - 300
T [°C] -10 to +110

Description:
Centred-disc butterfly valve, sealed by elastomer liner (EPDM XC), with manual gearbox to FM; semi-lug body (T2) suitable for downstream dismantling, valve disc made of nodular cast iron or stainless steel. Connections to EN.

Applications:
Fire protection



m

<http://shop.ksb.com/catalog/k0/en/product/ES000904>

ISORIA 10/16



PN [bar] 10/16
DN 10 - 1000
T [°C] -10 to +200

Description:
Centred-disc butterfly valve, sealed by elastomer liner, with lever or manual gearbox, pneumatic, electric or hydraulic actuator. Wafer-type body (T1), semi-lug body (T2), full-lug body (T4) or U-section body with flat faces (T5). Body types T2 and T4 are suitable for downstream dismantling and dead-end service with counterflange. Connections to EN, ASME, JIS.

Applications:
Shut-off and control duties in all industrial and energy sectors.



e, m, h, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000377>

ISORIA 20/25



PN [bar] 20/25
DN 32 - 1000
T [°C] -10 to +80

Description:
Centred-disc butterfly valve, sealed by elastomer liner, with lever or manual gearbox, pneumatic, electric or hydraulic actuator. Semi-lug body (T2), full-lug body (T4) or U-section body with flat faces (T5). Body types T2, T4 and T5 are suitable for downstream dismantling and dead-end service with counterflange. Connections to EN, ASME, JIS.

Applications:
Shut-off and control duties in all industrial and energy sectors.



e, m, h, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000379>

ISORIA 20 UL



PN [bar] max. 16
DN 40 - 700
T [°C] -10 to +80

Description:
Centred-disc butterfly valve, sealed by elastomer liner, with manual gearbox; semi-lug body (T2), full-lug body (T4). Body types T2 and T4 are suitable for downstream dismantling and dead-end service with counterflange. Connections to EN, ASME, JIS. Underwriter Laboratories (UL) approved.

Applications:
Fire protection



m

<http://shop.ksb.com/catalog/k0/en/product/ES000379>

MAMMOUTH



PN [bar] 6/10/16/20/25
DN 1050 - 4000
T [°C] 0 to +65

Description:

Centred-disc butterfly valve, sealed by elastomer liner, with manual gearbox, electric, hydraulic or counterweight actuator, U-section body with flat faces (T5), connections to EN, ASME or JIS.

Applications:

Water supply, water treatment, irrigation, drainage, desalination (reverse osmosis, multi-stage flash), industry. Cooling circuits and fire protection. Shipbuilding, steel industry and power stations (hydraulic, thermal, nuclear). Shut-off and control duties in all industrial sectors.



● e, m, p + AMTROBOX/AMTRONIC/SMARTONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000382>

KE PLASTOMER



PN [bar] 10
DN 40 - 600
T [°C] -20 to +200

Description:

Centred-disc butterfly valve for chemical applications, sealed by plastomer liner (PFA Teflon), with lever, manual gearbox, pneumatic or electric actuator, wafer-type body (T1), full-lug body (T4), U-section body with raised faces (T6), connections to EN, ASME, JIS.

Applications:

Highly corrosive applications: toxic and highly corrosive fluids which cannot be handled by metals and/or elastomers, thus requiring the sole use of PFA. Moderately corrosive applications: moderately aggressive fluids requiring the use of a PFA liner in combination with a stainless steel valve disc. Fluids requiring absolutely safe handling.



● e, m, h, p + AMTROBOX/AMTRONIC/SMARTONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000380>

KE ELASTOMER



PN [bar] 10
DN 40 - 300
T [°C] -20 to +150

Description:

Centred-disc butterfly valve for chemical applications, sealed by elastomer liner, with lever, manual gearbox, pneumatic, electric or hydraulic actuator, wafer-type body (T1), full-lug body (T4), connections to EN, ASME.

Applications:

Moderately corrosive and/or moderately abrasive industrial fluids; production of powdery products.



● e, m, h, p + AMTROBOX/AMTRONIC/SMARTONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000380>

Double-offset butterfly valves

APORIS-DEB02



PN 10/16/25
DN 150 - 2200
T [°C] -10 to +80

Description:

Double-offset butterfly valve with epoxy coating. Perfect shut-off in either flow direction. Flanged ends to EN standards, body and valve disc made of nodular cast iron.

Applications:

Shut-off or control duties; drinking water, seawater, air, water engineering.



● e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000824>

DANAIS 150



| | |
|----------|-------------|
| PN [bar] | max. 25 |
| or Class | 150 |
| DN | 50 - 1200 |
| T [°C] | -50 to +260 |

Description:
Double-offset butterfly valve, with plastomer seat (also in fire-safe design), metal seat or elastomer seat (FKM [VITON R] or NBR [Nitrile]). Lever or manual gearbox, pneumatic, electric or hydraulic actuator. Body made of nodular cast iron, cast steel, stainless steel or duplex stainless steel (254 SMO). Wafer-type body (T1), full-lug body (T4), T4 suitable for downstream dismantling and dead-end service. Connections to EN, ASME, JIS.

Applications:
Petroleum, gas, chemical and petrochemical industry, marine applications, transport of petroleum products and chemicals, sugar industry, geothermal energy, shipbuilding, low-pressure steam, vacuum service, mining, corrosive fluids, cleaning agents, highly aggressive fluids, brine, paper and pulp industry, fertilisers. All applications requiring offset disc butterfly valves.



e, m, h, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000427>

DANAIS MTII



| | |
|----------|-------------|
| PN [bar] | 25/50 |
| or Class | 150/300 |
| DN | 50 - 600 |
| T [°C] | -50 to +260 |

Description:
Double-offset butterfly valve with plastomer seat or metal seat (fire-safe), without gland packing, maintenance-free, with lever or manual gearbox, pneumatic, electric or hydraulic actuator, body made of steel or stainless steel. Wafer-type body (T1), full-lug body (T4) or flanged body (T7) with flat or raised faces. Body types T4 and T7 are suitable for dead-end service. Connections to EN, ASME or JIS. Certified to German TA-Luft Technical Guidelines on Air Quality Control.

Applications:
Petroleum, gas, chemical and petrochemical industry, nuclear power stations, onshore and offshore plants. Steam, vacuum and all applications requiring offset-disc butterfly valves.



e, m, h, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000381>

DANAIS TBTII



| | |
|----------|-------------|
| PN [bar] | 10/20 |
| or Class | 150 |
| DN | 50 - 1200 |
| T [°C] | -50 to +200 |

Description:
Double-offset butterfly valve for cryogenic applications; full-lug body (T4), flanged body (T7) with flat or raised faces, or body with butt weld ends made of stainless steel to ASME Class 150, JIS, fire-safe design. Degreased for oxygen service. Manual gearbox, pneumatic, electric or hydraulic actuator.

Applications:
Natural gas liquefaction, onshore and offshore plants. All liquefied gases.



e, m, h, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000815>

Triple-offset butterfly valves

TRIODIS 150



| | |
|----------|--------------|
| PN [bar] | max. 20 |
| or Class | 150 |
| DN | 80 - 1200 |
| T [°C] | -196 to +260 |

Description:
Triple-offset butterfly valve, metal-seated (fire-safe), without gland packing, maintenance-free, with lever or manual gearbox, pneumatic, electric or hydraulic actuator. Body made of steel or stainless steel, full-lug body (T4), flanged body (T7) with flat or raised faces, body with butt weld ends (BWSE). Body types T4 and T7 can be used for dead-end service. Connections to EN, ASME or JIS. Connections to ASME: Schedule 10S, 10, STD and XS to NPS for valves with butt weld ends (other connections on request). Fugitive emissions performance tested and certified to EN ISO 15848-1. Certified to German TA-Luft Technical Guidelines on Air Quality Control. Fire-safe design tested and certified to BS 6775-2. ATEX-compliant in accordance with Directive 2014/34/EU. In compliance with NACE MR0175 / ISO 15156 and MR 0103.

Applications:
Natural gas liquefaction. All liquefied gases. Heat transfer fluids, oil, gas, petrochemical industry, tank farms, refineries, onshore and offshore plants.



e, m, h, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000816>

TRIODIS 300



| | |
|----------|--------------|
| PN [bar] | max. 50 |
| or Class | 300 |
| DN | 80 - 1200 |
| T [°C] | -196 to +260 |

Description:

Triple-offset butterfly valve, metal-seated (fire-safe), without gland packing, maintenance-free, with lever or manual gearbox, pneumatic, electric or hydraulic actuator. Body made of steel or stainless steel, full-lug body (T4), flanged body (T7) with flat or raised faces, body with butt weld ends (BWSE). Body types T4 and T7 can be used for dead-end service. Connections to EN, ASME or JIS. Connections to ASME: Schedule 40S and STD to NPS for valves with butt weld ends (other connections on request). Fugitive emissions performance tested and certified to EN ISO 15848-1. Certified to German TA-Luft Technical Guidelines on Air Quality Control. Fire-safe design tested and certified to BS 6775-2. ATEX-compliant in accordance with Directive 2014/34/EU. In compliance with NACE MR0175 / ISO 15156 and MR 0103.

Applications:

Natural gas liquefaction. All liquefied gases. Heat transfer fluids, aggressive fluids, oil, gas, petrochemical industry, tank farms, refineries, onshore and offshore plants.



m, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000817>

TRIODIS 600



| | |
|----------|--------------|
| PN [bar] | max. 100 |
| or Class | 600 |
| DN | 150 - 1000 |
| T [°C] | -196 to +260 |

Description:

Triple-offset butterfly valve, metal-seated (fire-safe), without gland packing, maintenance-free, with lever or manual gearbox, pneumatic, electric or hydraulic actuator. Body made of steel or stainless steel, full-lug body (T4), flanged body (T7) with flat or raised faces. Body types T4 and T7 can be used for dead-end service. Connections to EN, ASME or JIS (other connections on request). Fugitive emissions performance tested and certified to EN ISO 15848-1. Certified to German TA-Luft Technical Guidelines on Air Quality Control. Fire-safe design tested and certified to BS 6775-2. ATEX-compliant in accordance with Directive 2014/34/EU. In compliance with NACE MR0175 / ISO 15156 and MR 0103.

Applications:

Natural gas liquefaction. All liquefied gases. Heat transfer fluids, aggressive fluids, oil, gas, petrochemical industry, tank farms, refineries, onshore and offshore plants.



m, p + AMTROBOX/AMTRONIC/SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000818>

Butterfly valves for nuclear applications

CLOSSIA



| | |
|------------------------|------------------|
| P _{max} [bar] | max. 5.5 |
| DN | 250/500/750/1000 |
| T [°C] | -20 to +170 |

Description:

Double-offset butterfly valve, metal-seated, maintenance-free. Steel body with one flanged and one weld end. With safety actuator with manual, pneumatic or electric actuation.

Applications:

In reactor containment of nuclear power stations.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000907>

Combined butterfly/check valve

DUALIS



DN 500 - 1400
T [°C] -10 to +65

Description:
Combined butterfly/check valve with single-acting hydraulically controlled counterweight actuator. For actuating valves of DN 500 to 1400.

Applications:
For installation in pump discharge lines in pumping stations. Power station cooling circuits. Protects pipelines and turbines.



<http://shop.ksb.com/catalog/k0/en/product/ES000905>

Single-piece ball valves

MP-CI/MP-II



PN 16
DN 15 - 150
T [°C] -10 to +200

Description:
Ball valve to DIN/EN with wafer-type body made of Kanigen-treated carbon steel (MP/CI) or stainless steel (MP/II), stainless steel ball, PTFE/graphite seat.

Applications:
Irrigation and fire-fighting systems, domestic water supply, air-conditioning systems, cooling circuits, water supply systems.



m, p + AMTROBOX/AMTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000625>

PROFIN-VT1



PN 40
DN 8 - 50
T [°C] -10 to +150

Description:
Ball valve to ANSI/ASME with threaded ends (BSP), single-piece body, reduced bore, solid ball, blowout-proof stem, body made of stainless steel.

Applications:
In spray irrigation systems, general irrigation systems, fire-fighting systems, air-conditioning systems, paint shops, snow-making systems, washing plants, water supply systems, mining, pressure boosting, chemical industry, process engineering, paper and pulp industry, domestic water supply, heating, ventilation and air-conditioning applications. For cleaning agents, condensate, cooling water, corrosive fluids, drinking water, fire-fighting water, lubricants, oil, river water, seawater, groundwater, service water, wash water and solvents.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000894>

Two-piece ball valves

ECOLINE BLT 150-300



Class 150 / 300
DN 15 - 300
T [°C] -10 to +200

Description:
Ball valve to ANSI/ASME with flanged ends, two-piece body, full bore, floating ball, elastomer sealing (also in fire-safe design).

Applications:
General industry, power stations, chemical industry, petrochemical industry and all related branches of industry, paper industry, food industry and pharmaceutical industry.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000795>

PROFIN-VT2L



| | |
|--------|-------------|
| PN | 40 |
| DN | 8 - 80 |
| T [°C] | -10 to +150 |

Description:

Ball valve to ANSI/ASME with threaded ends (BSP), two-piece body, full bore, solid ball, anti-static design, blowout-proof stem, body made of stainless steel.

Applications:

In spray irrigation systems, general irrigation systems, fire-fighting systems, air-conditioning systems, paint shops, snow-making systems, washing plants, water supply systems, mining, pressure boosting, chemical industry, process engineering, paper and pulp industry, domestic water supply, heating, ventilation and air-conditioning applications. For cleaning agents, condensate, cooling water, corrosive fluids, drinking water, fire-fighting water, lubricants, oil, river water, seawater, groundwater, service water, wash water and solvents.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000894>

Three-piece ball valves

ECOLINE BLC 1000



| | |
|--------|-------------|
| Class | 1000 WOG |
| DN | 8 - 100 |
| T [°C] | -10 to +200 |

Description:

Ball valve to ANSI/ASME with threaded ends (NPT), butt weld or socket weld ends, three-piece body, full bore, floating ball. Plastomer sealing (also in fire-safe design).

Applications:

General industry, power stations, chemical industry, petrochemical industry and all related branches of industry, paper industry, food industry and pharmaceutical industry.



m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000794>

PROFIN-SI3FIT/-SI3IT/-SI3LIT



| | |
|--------|-------------|
| PN | 16/40 |
| DN | 15 - 100 |
| T [°C] | -10 to +150 |

Description:

Ball valve to ANSI/ASME with flanged ends, threaded ends (BSP) or long butt weld ends, three-piece body, full bore, solid ball, top flange to ISO 5211, anti-static design, blowout-proof stem, spring-loaded stem seal, body made of stainless steel.

Applications:

In spray irrigation systems, general irrigation systems, fire-fighting systems, air-conditioning systems, paint shops, snow-making systems, washing plants, water supply systems, mining, pressure boosting, chemical industry, process engineering, paper and pulp industry, domestic water supply, heating, ventilation and air-conditioning applications. For cleaning agents, condensate, cooling water, corrosive fluids, drinking water, fire-fighting water, lubricants, oil, river water, seawater, groundwater, service water, wash water and solvents.



m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000893>

PROFIN-VT3/-VT3L/-VT3F/-VT33L



| | |
|--------|-------------|
| PN | 16/40 |
| DN | 8 - 100 |
| T [°C] | -10 to +150 |

Description:

Ball valve to ANSI/ASME with flanged ends, threaded ends (BSP) or long butt weld ends, three-piece body, full bore, solid ball, blowout-proof stem, body made of stainless steel.

Applications:

In spray irrigation systems, general irrigation systems, fire-fighting systems, air-conditioning systems, paint shops, snow-making systems, washing plants, water supply systems, mining, pressure boosting, chemical industry, process engineering, paper and pulp industry, domestic water supply, heating, ventilation and air-conditioning applications. For cleaning agents, condensate, cooling water, corrosive fluids, drinking water, fire-fighting water, lubricants, oil, river water, seawater, groundwater, service water, wash water and solvents.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000894>

Soft-seated diaphragm valves to DIN/EN

SISTO-KB



PN 10
DN 15 - 200
T [°C] -20 to +140

Description:
Diaphragm valve to DIN/EN with flanged ends; shut-off and sealing to atmosphere by diaphragm; straight-way pattern, body with or without lining, position indicator with integrated stem protection. DN 125 to DN 200 with threaded bush. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In building services, industrial plants, power stations; suitable for abrasive and aggressive products such as service water, waste water, acids, alkaline solutions, sludges and suspensions.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000314>

SISTO-KBS



PN 10
DN 15 - 200
T [°C] -20 to +140

Description:
Diaphragm valve to DIN/EN with flanged ends, short face-to-face length; shut-off and sealing to atmosphere by diaphragm; straight-way pattern, body with or without lining, position indicator with integrated stem protection. DN 125 to DN 200 with threaded bush. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In building services, industrial plants, power stations; suitable for abrasive and aggressive products such as service water, waste water, acids, alkaline solutions, sludges and suspensions.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000526>

SISTO-10



PN 10
DN 15 - 300
T [°C] -20 to +160

Description:
Diaphragm valve to DIN/EN with flanged ends; shut-off and sealing to atmosphere by spiral-supported diaphragm (DN 65 and above); body with or without lining, position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In industrial and chemical plants, in process engineering. Suitable for service water, air, oil, abrasive and aggressive fluids.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000315>

SISTO-10M



PN 10
DN 15 - 80
T [°C] -10 to +140

Description:
Diaphragm valve to DIN/EN with threaded sockets; shut-off and sealing to atmosphere by spiral-supported diaphragm (DN 65 and above); position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In industrial and chemical plants, in process engineering. Suitable for service water, air, oil, abrasive and aggressive fluids.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000513>

SISTO-16



PN 16
DN 15 - 200
T [°C] -10 to +160

Description:
Diaphragm valve to DIN/EN with flanged ends; shut-off and sealing to atmosphere by completely enclosed spiral-supported diaphragm; body with or without lining, position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In building services, industrial plants and power stations; suitable for drinking water, service water, air, oil, technical gases; from fluids handled in the food and beverages industry to abrasive and aggressive products in chemical and process engineering.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000316>

SISTO-16S



| | |
|--------|-------------|
| PN | 16 |
| DN | 15 - 200 |
| T [°C] | -20 to +160 |

Description:
Diaphragm valve to DIN/EN with flanged ends, short face-to-face length; shut-off and sealing to atmosphere by completely enclosed spiral-supported diaphragm; body with or without lining, position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In building services, industrial plants and power stations; suitable for drinking water, service water, air, oil, technical gases; from fluids handled in the food and beverages industry to abrasive and aggressive products in chemical and process engineering.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000514>

SISTO-16RGA



| | |
|--------|------------|
| PN | 16 |
| DN | 15 - 80 |
| T [°C] | -10 to +90 |

Description:
Diaphragm valve to DIN/EN with gunmetal body and threaded sockets for drinking water installations in building services to DIN 1988, DIN-DVGW-approved for water acc. to test W 270, in compliance with KTW recommendations (use of elastomers in drinking water applications); shut-off and sealing to atmosphere by completely enclosed diaphragm; position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
Drinking water, particularly drinking water installations to DIN 1988, seawater, all service water qualities.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000319>

SISTO-16TWA/HWA/DLU



| | |
|--------|-------------|
| PN | 16 |
| DN | 15 - 200 |
| T [°C] | -10 to +140 |

Description:
Diaphragm valve to DIN/EN with flanged ends, for drinking water installations to DIN 1988, DIN-DVGW-approved for water acc. to test W 270, in compliance with KTW recommendations (use of elastomers in drinking water applications); shut-off and sealing to atmosphere by completely enclosed diaphragm; position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
SISTO-16TWA (drinking water up to 90 °C): drinking water, particularly drinking water installations to DIN 1988, water containing chlorine, seawater, etc. SISTO-16HWA (hot water up to 140 °C): all service water qualities. SISTO-16 DLU (compressed air up to 90 °C): compressed air with oil content, oils and technical gases.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000318>

SISTO-20



| | |
|--------|-------------|
| PN | 16 |
| DN | 15 - 200 |
| T [°C] | -20 to +160 |

Description:
Diaphragm valve to DIN/EN with flanged ends; shut-off and sealing to atmosphere by completely enclosed spiral-supported diaphragm; body with or without lining, position indicator with integrated stem protection. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
In building services, industrial plants and power stations; suitable for drinking water, service water, air, oil, technical gases; from fluids handled in the food and beverages industry to abrasive and aggressive products in chemical and process engineering.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000317>

SISTO-C



| | |
|--------|-------------|
| PN | 16 |
| DN | 6 - 100 |
| T [°C] | -20 to +160 |

Description:
Diaphragm valve with butt weld ends or clamps; in straight-way, Y or T pattern, or as a multi-port valve; shut-off and sealing to atmosphere by completely enclosed diaphragm. No dead volumes, suitable for sterilisation, SIP/CIP-compliant design, visual position indicator. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:
Biotechnology, pharmaceutical industry, sterile processes, food and beverages industry.



m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000320>

Diaphragm valves for nuclear applications

SISTO-20NA



PN 20
DN 8 - 150
T [°C] max. +100

Description:

Diaphragm valve for nuclear applications, with butt weld ends; shut-off and sealing to atmosphere by completely enclosed spiral-supported diaphragm. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:

Cleaning systems, condensate and cooling water systems, waste water systems, auxiliary systems.



e, m, p

<http://shop.ksb.com/catalog/k0/en/product/ES000840>

SISTO-DrainNA



PN 16
DN 15 - 25
T [°C] max. +100

Description:

Diaphragm valve for nuclear applications, with butt weld ends; shut-off and sealing to atmosphere by completely enclosed spiral-supported diaphragm. All moving parts are separated from the fluid by the diaphragm. Maintenance-free.

Applications:

Heating systems, air-conditioning systems, auxiliary systems.



m

<http://shop.ksb.com/catalog/k0/en/product/ES000841>

Feed water bypass valves

ZJSVM/RJSVM



PN Approx. 600 bar
DN 100 - 800
T [°C] -10 to +450

Description:

Feed water bypass valve to DIN/EN with butt weld ends, pressure seal design, billet-forged body, Z or T pattern, seat/disc interface made of wear and corrosion resistant Stellite, controlled by process fluid.

Applications:

In industrial plants, power stations, process engineering and shipbuilding. For water and steam. Other non-aggressive fluids such as gas or oil on request.

e, m, p

Expansion and anti-vibration joints

ECOLINE GE1/GE2/GE3



PN 16
DN 15 - 300
T [°C] -10 to +105

Description:

Expansion joint to DIN/EN with flanged or threaded ends, made of EPDM elastomer or NBR, flanges made of nickel-coated carbon steel.

Applications:

Irrigation, domestic water supply, air-conditioning systems, cooling circuits, food and beverages industry, water treatment, water supply.



□

<http://shop.ksb.com/catalog/k0/en/product/ES000687>

ECOLINE GE4



| | |
|--------|-------------|
| PN | 16 |
| DN | 20 - 200 |
| T [°C] | -10 to +100 |

Description:
Anti-vibration joint to DIN/EN, body made of EPDM, flanges to EN standards.



Applications:
Irrigation, domestic water supply, air-conditioning systems, cooling circuits, food and beverages industry, water treatment, water supply.





<http://shop.ksb.com/catalog/k0/en/product/ES000681>

Levers

CR/CM

| | | | |
|---|---|--|---|
|  | <p>T [°C] -20 to +80</p> | <p>Description: Lever made of ductile cast iron. CR type series: locks in 10 positions (open, closed and 8 evenly spaced intermediate positions) and CM type series: same as CR, with special coating.</p> <p>Applications: All applications in building services, water, energy and industrial engineering.</p> |  |
| http://shop.ksb.com/catalog/k0/en/product/ES000501 | | | |

S/SR/SP




| | | | |
|---|---|---|---|
|  | <p>T [°C] -20 to +80</p> | <p>Description: Lever made of light metal alloy; type series S: locks in limit positions (open and closed), type series SR: locks in 9 positions (open, closed and 7 evenly spaced intermediate positions), type series SP: locks in any position.</p> <p>Applications: All applications in water, energy and industrial engineering.</p> |  |
| http://shop.ksb.com/catalog/k0/en/product/ES000501 | | | |

Manual gearboxes

MN



| | | | |
|---|---|--|---|
|  | <p>Output torque [Nm] max. 800 Enclosure IP67 T [°C] -40 to +120</p> | <p>Description: Manual actuator for operating quarter-turn valves. MN range manual gearbox, irreversible worm gear kinematics, handwheel-operated.</p> <p>Applications: Building services, general industrial processes, water and industrial applications in non-corrosive and non-saline environments.</p> |  |
| http://shop.ksb.com/catalog/k0/en/product/ES000503 | | | |

MR



| | | | |
|---|--|--|---|
|  | <p>Output torque [Nm] max. 16,000 Enclosure IP67/IP68 T [°C] -50 to +80</p> | <p>Description: Heavy-duty manual actuator for operating quarter-turn valves. MR range manual gearbox, irreversible worm gear or scotch-yoke kinematics. Handwheel-operated as standard. Models MR 400 to 1600 can be fitted with actuators. Options include alternative operating mechanisms, limit switch boxes, low-temperature version, etc.</p> <p>Applications: Building services, industry and process engineering, water and waste water management, energy, petroleum and natural gas, mining, dredgers and shipbuilding.</p> |  |
|  http://shop.ksb.com/catalog/k0/en/product/ES000502 | | | |

Electric actuators



ACTELEC (BERNARD CONTROLS)

| | | | | |
|---|-----------------------|-------------|--|---|
|  | Quarter-turn actuator | EZ4 - SQ120 | Description: Electric actuators by BERNARD CONTROLS for direct mounting on quarter-turn valves (actuator flange to ISO 5211) or linear valves in conjunction with a manual gearbox of the MR type series (actuator flange to ISO 5210). Power supply: single-phase AC, three-phase or direct current. Torque switch, travel stop and limit switch box as standard. For on/off or control duties. Integrated local control or remote control. |  |
| | Multi-turn actuator | 31 - 800 | | |
| | Enclosure | IP67 | Applications: All applications in water engineering, energy and industrial engineering. | |
| | Output torque [Nm] | max. 8,000 | | |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000407 | |

ACTELEC (AUMA)



| | | | | |
|---|-----------------------|-----------------|--|---|
|  | Quarter-turn actuator | SQ 05.2 - SQ 12 | Description: Electric actuators by AUMA for direct mounting on quarter-turn valves (actuator flange to ISO 5211) or linear valves in conjunction with a manual gearbox of the MR type series (actuator flange to ISO 5210). Power supply: single-phase AC, three-phase or direct current. Torque switch, travel stop and limit switch box as standard. For on/off or control duties. Integrated local control or remote control. |  |
| | Multi-turn actuator | 31 - 1600 | | |
| | Enclosure | IP67 | Applications: All applications in water engineering, energy and industrial engineering. | |
| | Output torque [Nm] | max. 16,000 | | |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000407 | |

SISTO-LAE

| | | | | |
|---|---------------------|----------|--|---|
|  | Type | AUMA | Description: Multi-turn actuators for valves with rising stem, max. closing force 60,000 N, configurable as a function of flow characteristics and valve travel; open/closed position feedback; factory-mounted. |  |
| | Multi-turn actuator | | | |
| | Enclosure | IP67 | Applications: Building services, industry, power stations, food industry, chemical industry. | |
| | Output torque [Nm] | max. 250 | | |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000405 | |

Hydraulic actuators

HQ

| | | | | |
|---|--------------------|-------------|--|---|
|  | Output torque [Nm] | max. 55,000 | Description: Single-acting or double-acting hydraulic actuator (gas cartridge or spring) for mounting on quarter-turn valves (butterfly valves or ball valves). Actuator flange to ISO 5211. Control pressure up to 160 bar. Mounts on valve stems with square end or flat end. Force transmission via rack-and-pinion or scotch-yoke kinematics provides output torques of up to 55,000 Nm which are ideal for actuating quarter-turn valves. Equipped with a visual position indicator and adjustable travel stops for open/closed position as standard. Optional manual override. Can be equipped with a hydraulic power unit: for shut-off, as a safety block, ESD block, as a bypass device enabling manual override. Can be combined with all limit switch boxes of the AMTROBOX/AMTROBOX R type series. |  |
| | Enclosure | IP68 | | |
| | T [°C] | -20 to +100 | Applications: Marine | |
| | | | | http://shop.ksb.com/catalog/k0/en/product/ES000924 |

● AMTROBOX

Pneumatic actuators

ACTAIR



| | |
|---|-------------|
| Output torque [Nm] at a control pressure of 6 bar | max. 16,000 |
| Enclosure | IP67 |
| T [°C] | -20 to +80 |

Description:

Double-acting pneumatic actuator for mounting on quarter-turn valves (butterfly valves or ball valves). Actuator flange to ISO 5211. Control pressure up to 8 bar. Mounts on valve stems with square end, flat end or key. Force transmission via rack-and-pinion, scotch-yoke or patented AMRI yoke kinematics provides output torques of up to 16,000 Nm which are ideal for actuating quarter-turn valves. Equipped with a visual position indicator and adjustable travel stops for open/closed position as standard. Optional manual override. Suitable for mounting control unit type series AMTROBOX, AMTRONIC, SMARTRONIC or any other device with an interface to VDI/VDE 3845.

Applications:

All applications in water, energy and industrial engineering.



AMTROBOX, AMTRONIC, SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000411>

ACTAIR NG



| | |
|---|------------|
| Output torque [Nm] at a control pressure of 6 bar | max. 8,000 |
| Enclosure | IP67 |
| T [°C] | -20 to +80 |

Description:

Double-acting pneumatic actuator for mounting on quarter-turn valves (butterfly valves or ball valves). Actuator flange to ISO 5211. Control pressure up to 8 bar. Mounts on valve stems with square end or flat end. Force transmission via scotch-yoke kinematics provides output torques of up to 8000 Nm which are ideal for actuating quarter-turn valves. Equipped with a visual position indicator and adjustable travel stops for open/closed position as standard. Optional manual override. Suitable for mounting control unit type series AMTROBOX, AMTRONIC, SMARTRONIC or any other device with an interface to VDI/VDE 3845.

Applications:

All applications in water engineering, energy and industrial engineering.



AMTROBOX, AMTRONIC, SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000411>

DYNACTAIR



| | |
|---|------------|
| Output torque [Nm] at a control pressure of 6 bar | max. 8,000 |
| Enclosure | IP65 |
| T [°C] | -20 to +80 |

Description:

Single-acting pneumatic actuator for mounting on quarter-turn valves (butterfly valves or ball valves). Actuator flange to ISO 5211. Control pressure up to 8 bar. Mounts on valve stems with square end, flat end or key. Force transmission via rack-and-pinion, scotch-yoke or patented AMRI yoke kinematics provides output torques of up to 8000 Nm which are ideal for actuating quarter-turn valves. Reset to fail-safe position in case of control air failure is effected by means of spring assemblies. Equipped with a visual position indicator and adjustable travel stops for open/closed position as standard. Manual override can be provided up to DYNACTAIR 100 on request. Suitable for mounting control unit type series AMTROBOX, AMTRONIC, SMARTRONIC or any other device with an interface to VDI/VDE 3845.

Applications:

All applications in water, energy and industrial engineering.



AMTROBOX, AMTRONIC, SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000412>

DYNACTAIR NG



| | |
|---|--------------------|
| Output torque [Nm] at a control pressure of 6 bar | max. 4,000 |
| Enclosure T [°C] | IP65 -20 to +80 |

Description:
Single-acting pneumatic actuator for mounting on quarter-turn valves (butterfly valves or ball valves). Actuator flange to ISO 5211. Control pressure up to 8 bar. Mounts on valve stems with square end or flat end. Force transmission via scotch-yoke kinematics provides output torques of up to 4000 Nm which are ideal for actuating quarter-turn valves. Reset to fail-safe position in case of control air failure is effected by means of spring assemblies. Equipped with a visual position indicator and adjustable travel stops for open/closed position as standard. Optional manual override. Suitable for mounting control unit type series AMTROBOX, AMTRONIC, SMARTRONIC or any other device with an interface to VDI/VDE 3845.

Applications:
All applications in water engineering, energy and industrial engineering.



● AMTROBOX, AMTRONIC, SMARTRONIC

<http://shop.ksb.com/catalog/k0/en/product/ES000412>

SISTO-LAD



| | |
|----------------------------|-------------|
| Control air pressure [bar] | max. 6 |
| Closing force [N] | max. 20,000 |

Description:
Diaphragm actuator in compact design for mounting on valves with a linear stem movement (globe, diaphragm and gate valves). Available in single-acting spring-to-close or spring-to-open design, or double-acting air-to-open/air-to-close design; suitable for mounting limit switches or positioners to suit customer requirements, factory-mounted. Settings are adjusted during factory test run.

Applications:
In building services, industrial plants, power stations; suitable for abrasive and aggressive products such as service water, waste water, acids, alkaline solutions, sludges and suspensions.



<http://shop.ksb.com/catalog/k0/en/product/ES000805>

SISTO-LAP



| | |
|----------------------------|--------------|
| Control air pressure [bar] | max. 10 |
| Closing force [N] | max. 250,000 |

Description:
Piston actuator in heavy-duty design for mounting on valves with a linear stem movement (globe, diaphragm and gate valves). Mounting flange to DIN/ISO 5210, available in single-acting spring-to-close or spring-to-open design, or double-acting air-to-open/air-to-close design; suitable for mounting limit switches or positioners to suit customer requirements, factory-mounted. Settings are adjusted during factory test run.

Applications:
In building services, industrial plants, power stations, the food and beverages industries and the chemical industry. The pneumatic actuators can also be used in potentially explosive atmospheres.



<http://shop.ksb.com/catalog/k0/en/product/ES000409>

SISTO-C LAP



| | |
|----------------------------|-------------|
| Control air pressure [bar] | max. 10 |
| Closing force [N] | max. 20,000 |

Description:
Piston actuator in high-grade stainless steel design for use on SISTO-C diaphragm valves. Available in single-acting spring-to-close or spring-to-open design, or double-acting air-to-open/air-to-close design; suitable for mounting limit switches or positioners to suit customer requirements, factory-mounted. Settings are adjusted during factory test run.



Applications:
Biotechnology, pharmaceutical industry, sterile processes, food and beverages industry.



<http://shop.ksb.com/catalog/k0/en/product/ES000320>



Actuator accessories

RMD



| | | | | |
|---|---------------------|--------------------|--|---|
|  | Enclosure T [°C] | IP65 -20 to +80 | Description: Manual override using a declutchable gear operator with handwheel for mounting on ACTAIR / ACTAIR NG double-acting pneumatic actuators, DYNACTAIR / DYNACTAIR NG single-acting pneumatic actuators, and HQ single-acting or double-acting hydraulic actuators. The manual override is fitted between the valve and the actuator. The manual override has priority over the pneumatic or hydraulic actuator and is locked either in clutched or declutched position using the locking device. Applications: All applications in water, energy and industrial engineering. |  |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000906 | |

Monitoring



AMTROBOX

| | | | | |
|---|-----------------------------|----------------------------|--|---|
|  | <p>Enclosure T [°C]</p> | <p>IP67 -20 to +80</p> | <p>Description: Multi-functional AMTROBOX limit switch box. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX (R1149) mounts on MR manual gearboxes, ACTAIR and ACTAIR NG pneumatic actuators and HQ hydraulic actuators.</p> <p>Applications: All applications in water engineering, building services and energy engineering.</p> |  |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000463 | |



AMTROBOX EEx ia

| | | | | |
|---|-----------------------------|----------------------------|--|---|
|  | <p>Enclosure T [°C]</p> | <p>IP67 -20 to +80</p> | <p>Description: Multi-functional AMTROBOX limit switch box. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX EEx ia (R1172): intrinsically safe version for potentially explosive atmospheres.</p> <p>Applications: All applications in water engineering, building services and energy engineering.</p> |  |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000463 | |



AMTROBOX ATEX Zone 22

| | | | | |
|---|-----------------------------|----------------------------|--|---|
|  | <p>Enclosure T [°C]</p> | <p>IP67 -10 to +60</p> | <p>Description: Multi-functional AMTROBOX limit switch box. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX ATEX (X1140, X1149): ATEX-compliant version for potentially explosive dust atmospheres (Zone 22).</p> <p>Applications: All applications in water engineering, building services and energy engineering.</p> |  |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000463 | |

AMTROBOX C

| | | | | |
|---|-----------------------------|----------------------------|---|---|
|  | <p>Enclosure T [°C]</p> | <p>IP65 -20 to +80</p> | <p>Description: Cost-effective solution for open/closed position signalling via mechanical limit switches. AMTROBOX C (RA01290) mounts on ACTAIR/ACTAIR NG pneumatic actuators, MR manual gearboxes to VDI/VDE and BOAX-B Mat P valves.</p> <p>Applications: All applications in water engineering, building services and energy engineering.</p> |  |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000463 | |

AMTROBOX M

| | | | | |
|---|-----------------------------|----------------------------|--|---|
|  | <p>Enclosure T [°C]</p> | <p>IP65 -20 to +80</p> | <p>Description: Limit switch box specially designed for manual actuation. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX M mounts on the S series of quarter-turn levers (R1020) and manual gearbox types MA 12 and MA 25 (R1021).</p> <p>Applications: All applications in water engineering, building services and energy engineering.</p> |  |
| | | | http://shop.ksb.com/catalog/k0/en/product/ES000463 | |

AMTROBOX R



Enclosure
T [°C]

IP68
-20 to +70

Description:
Sturdy and multi-functional. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX R (R1187) mounts on MR manual gearboxes, ACTAIR/ACTAIR NG pneumatic actuators, HQ hydraulic actuators and any actuators with VDI/VDE interface.

Applications:
All applications in water engineering, energy engineering, offshore and heavy industry.



<http://shop.ksb.com/catalog/k0/en/product/ES000463>

AMTROBOX R EEx ia



Enclosure
T [°C]

IP68
-25 to +80

Description:
Sturdy and multi-functional. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX R EEx ia (R1188): intrinsically safe version for explosive atmospheres (Zones 0 + 20).

Applications:
All applications in water engineering, energy engineering, offshore and heavy industry.



<http://shop.ksb.com/catalog/k0/en/product/ES000463>

AMTROBOX R Ex d



Enclosure
T [°C]

IP68
-25 to +80

Description:
Sturdy and multi-functional. For open/closed position signalling via mechanical limit switches or proximity sensors. AMTROBOX R Exd (R1189): intrinsically safe version for potentially explosive atmospheres.

Applications:
All applications in water engineering, energy engineering, offshore and heavy industry.



<http://shop.ksb.com/catalog/k0/en/product/ES000463>

ON/OFF valve controllers

AMTRONIC



Enclosure
Control air pressure [bar]
T [°C]

IP67
3 to 8
-20 to +80

Description:
On/off control of pneumatic quarter-turn actuators and open/closed position signalling. Mounts directly on ACTAIR/DYNACTAIR or ACTAIR NG actuators with no need for a bracket, providing a rugged, compact and integrated solution. Its integrated directional control valve eliminates the need for any pneumatic lines between AMTRONIC and the actuator. The actuating time of the actuator can be set via AMTRONIC's air flow reducer. AMTRONIC can be connected to Profibus DP and AS-i field buses. AMTRONIC has been specially developed to reduce control unit cabling. Connection via field bus enables both power supply and control information exchange with the process control system. AMTRONIC can be integrated in field bus environments with Profibus DP protocol and especially AS-i protocol. The intrinsically safe AMTRONIC Ex ia version can be operated in potentially explosive atmospheres. It complies with ATEX directive 2014/34/EU and is marked to CE 0081 Ex II 1 G. Type of protection EEx-ia IIC T6 as per EN 50014 and EN 50020.

Applications:
All applications in water, energy and industrial engineering.



<http://shop.ksb.com/catalog/k0/en/product/ES000462>

Positioners

SMARTRONIC MA



Enclosure IP67
Control air pressure [bar] 2 to 7
T [°C] -20 to +80

Description:
SMARTRONIC MA (R1310) is an electro-pneumatic digital positioner powered via the 4-20 mA signal. Mounts on ACTAIR/DYNACTAIR actuators with direct compressed air supply, or on any type of quarter-turn actuator with VDI/VDE 3845 interface and linear actuators with NAMUR interface. SMARTRONIC MA reduces investment, commissioning and operating costs as the unit consumes no air while idle.

Applications:
All applications in water, energy and industrial engineering.



<http://shop.ksb.com/catalog/k0/en/product/ES000461>

SMARTRONIC AS-i



Enclosure IP67
Control air pressure [bar] 3 to 8
T [°C] -20 to +80

Description:
SMARTRONIC AS-i is an electro-pneumatic digital positioner for connection to an AS-i field bus. Certified by AS International. Mounts on ACTAIR/DYNACTAIR actuators with direct compressed air supply, or on any type of quarter-turn actuator with VDI/VDE 3845 interface and linear actuators with NAMUR interface.

Applications:
All applications in water, energy and industrial engineering.



<http://shop.ksb.com/catalog/k0/en/product/ES000874>

Intelligent positioners

SMARTRONIC PC



Enclosure IP67
Control air pressure [bar] 3 to 8
T [°C] -20 to +80

Description:
SMARTRONIC PC (R1312) is an intelligent, compact and innovative positioner. The integrated control offered by this multi-functional control unit represents the latest in open-loop and closed-loop control technology for valves. The unit attaches directly to ACTAIR or DYNACTAIR actuators with no need for a bracket or external piping, providing a rugged, compact and integrated solution. SMARTRONIC PC offers four functions: programmable curves for valve opening and closing, intelligent positioning, process monitoring and control. SMARTRONIC PC is PC programmable and can be connected to a Profibus DP field bus.

Applications:
All applications in water, energy and industrial engineering.



<http://shop.ksb.com/catalog/k0/en/product/ES000873>



Technology that **makes its mark**

Your local KSB representative:



The KSB newsletter –
don't miss out, sign up now:
www.ksb.com/newsletter



KSB Aktiengesellschaft
Johann-Klein-Str. 9
67227 Frankenthal (Germany)
www.ksb.com

You can also visit us at
www.ksb.com/socialmedia